

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated](#)

[IMT4-7-F](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)




## Features

- Epitaxial Planar Die Construction
- Complementary NPN Type Available (IMX8)
- Small Surface Mount Package
- Lead Free/RoHS Compliant (Note 3)**
- "Green" Device, Note 4 and 5

## Mechanical Data

- Case: SOT-26
- Case Material: Molded Plastic, "Green" Molding Compound, Note 5. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Copper leadframe).
- Marking Information: KX7 - See Page 3
- Ordering & Date Code Information: See Page 3
- Weight: 0.016 grams (approximate)



SOT-26			
Dim	Min	Max	Typ
<b>A</b>	0.35	0.50	0.38
<b>B</b>	1.50	1.70	1.60
<b>C</b>	2.70	3.00	2.80
<b>D</b>	—	—	0.95
<b>F</b>	—	—	0.55
<b>H</b>	2.90	3.10	3.00
<b>J</b>	0.013	0.10	0.05
<b>K</b>	1.00	1.30	1.10
<b>L</b>	0.35	0.55	0.40
<b>M</b>	0.10	0.20	0.15
$\alpha$	0°	8°	—

**All Dimensions in mm**

## Maximum Ratings

$\text{@ } T_A = 25^\circ\text{C}$  unless otherwise specified

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	-120	V
Collector-Emitter Voltage	$V_{CEO}$	-120	V
Emitter-Base Voltage	$V_{EBO}$	-5.0	V
Collector Current - Continuous	$I_C$	-50	mA
Power Dissipation (Note 1)	$P_d$	225	mW
Thermal Resistance, Junction to Ambient (Note 1)	$R_{\theta JA}$	555	°C/W
Operating and Storage Temperature Range	$T_j, T_{STG}$	-55 to +150	°C

## Electrical Characteristics

$\text{@ } T_A = 25^\circ\text{C}$  unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS (Note 2)</b>						
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-120	—	—	V	$I_C = -50\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-120	—	—	V	$I_C = -1.0\text{mA}$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5.0	—	—	V	$I_E = -50\mu\text{A}$
Collector Cutoff Current	$I_{CBO}$	—	—	-0.5	$\mu\text{A}$	$V_{CB} = -100\text{V}$
Emitter Cutoff Current	$I_{EBO}$	—	—	-0.5	$\mu\text{A}$	$V_{EB} = -4.0\text{V}$
<b>ON CHARACTERISTICS (Note 2)</b>						
DC Current Gain	$h_{FE}$	180	—	820	—	$I_C = -2.0\text{mA}, V_{CE} = -6.0\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	—	—	-0.5	V	$I_C = -10\text{mA}, I_B = -1.0\text{mA}$
<b>SMALL SIGNAL CHARACTERISTICS</b>						
Current Gain-Bandwidth Product	$f_T$	—	140	—	MHz	$V_{CE} = -12\text{V}, I_C = -2.0\text{mA}, f = 100\text{MHz}$







Notes:

- Device mounted on FR-5 PCB 1.0 x 0.75 x 0.062 inch pad layout as shown on Diodes Inc. suggested pad layout AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>. 200mW per element must not be exceeded.
- Short duration pulse test used to minimize self-heating effect.
- No purposefully added lead.
- Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
- Product manufactured with Date Code 0627 (week 27, 2006) and newer are built with Green Molding Compound. Product manufactured prior to Date Code 0627 are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.



**PART OBSOLETE – USE DMMT5401**

OBSOLETE – PART DISCONTINUED






**PART OBSOLETE – USE DMMT5401**

**Ordering Information** (Note 5 & 6)

Device	Packaging	Shipping
IMT4-7-F	SOT-26	3000/Tape & Reel

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



KX7 = Product Type Marking Code

YM = Date Code Marking

Y = Year ex: T = 2006

M = Month ex: 9 = September

YM = Date Code Marking

Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.