

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[E-Switch](#)
[EG1381A](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



E-SWITCH™

SERIES EG1381 SWITCHES

SLIDE SWITCHES



FEATURES & BENEFITS

Tape & Reel Packaging
 3-position
 Surface Mount
 Sub-miniature

APPLICATIONS / MARKETS

Computer Servers/peripherals
 Consumer electronics
 Instrumentation
 Test & measurement

MECHANICAL SPECIFICATIONS

Mechanical Life:	10,000 cycles
Force:	250 +/- 100 gf to center position 300 +/- 150 gf from center position
Travel:	2.0 +/- 0.1mm each position

ELECTRICAL SPECIFICATIONS

Electrical Life:	10,000 cycles
Contact Rating:	300mA @ 6VDC
Contact Resistance:	70mΩ (initial max)
Insulation Resistance:	100MΩ (Min @ 500VDC)
Dielectric Strength:	500VAC

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature:	-10°C to +60°C
Storage Temperature:	-20°C to +70°C

HOW TO ORDER:

