

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Amphenol Commercial Products](#)
[5720240](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without the prior consent, and that no right is granted to disclose or to use any information in this document.

REVISIONS				
SYM	RCN	DESCRIPTION	DATE	APPROVED
A	HK	PRELIMINARY RELEASE	01/13/03	Y.M.LEE
B	HK	ADD CHOP OF ROHS	9/11/06	IP

RIVET BUSHING TO SHELL AS SHOWN
BUSHING MUST FLOAT FREELY 0.020
IN. IN ALL DIRECTIONS FROM
MOUNTING CENTER






TABLE 1

CONNECTOR SIZES	AVERAGE MATING FORCE (POUNDS)
14	5
24	8
36	12
50	15
64	19

SPECIFICATIONS:

- 1) SOLDER CUP CONTACT: TO ACCOMMODATE 22-30 AWG SOLID AND 24-30 STRANDED CONNECTOR WIRES.
- 2) DIELECTRIC: DIALYL-PHTHALATE PER MIL-M-14F TYPE MDG UL-94V0
- 3) CONTACT MATERIAL: COPPER ALLOY
- 4) CONTACT: 20 MICRO-INCHES MIN. GOLD MATING AREA: 3-5 MICRO-INCHES GOLD TERMINAL AREA: 50 MICRO-INCHES MIN. NICKEL UNDERPLATING ALL OVER.
- 5) SHELL MATERIAL: ZINC PLATED STEEL WITH CLEAR CHROMATE COATING
- 6) CURRENT CAPACITY: 5 AMPS/CONTACT
- 7) VOLTAGE RATING: 700 VOLTS D.C. AT SEA LEVEL
200 VOLTS D.C. AT 70,000 FEET
- 8) INSULATION RESISTANCE: >5000 M OHM
- 9) DIELECTRIC WITHSTANDING VOLTAGE: 1200 VAC (RMS) AT SEA LEVEL
- 10) CONNECTOR MATING FORCE: REFER TO TABLE 1.

- 11) CONTACT RETENTION FORCE: 2 LBS MAX.
- 12) DURABILITY: 250 CYCLES MIN.
- 13) VIBRATION: NO INTERRUPTIONS < 1u SEC.
- 14) OPERATING TEMPERATURE: -55°C TO +105°C
(-67°F TO +221°F)

CUSTOMER INFORMATION DRAWING

ITEM NO	NOMENCLATURE OR DESCRIPTION	QTY REQ'D
PARTS LIST		
UNLESS OTHERWISE SPECIFIED TOLERANCES U.S. METRIC X +/- .015 XX +/- .010 XXX +/- .005 FRACTIONS +/- 1" ANGLES +/- 1° FOR MATERIALS AND FINISHES SEE NOTE REMOVE SHARP EDGES		APPROVAL DRAWN XS.GVO CHECKED DATE 9/11/06 CHECKED
DRAWING FILE: DRAWING 57/C5720240.DWG		TITLE 24 SIZE RECEPTACLE ASSY, RACK & PANEL MINIATURE RIBBON
DIMENSIONS U.S. INCHES (METRIC) (MM)		ANGLE OF PROJECTION
SIZE A3		DRAWING NO. C57-20240
SCALE NONE		REV. B
SHEET 1 OF 1		