

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)
[AT-S-26-6/4/S-25/R](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7	
A								

Note for plug:

- Material: Housing-polycarbonate, clear.
- Terminal-0.36[.014] thick phosphor bronze.
- Thick gold in localized gold plate.
- Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/4/S-5/R	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-6/4/S-7/R	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-6/4/S-10/R	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-6/4/S-12/R	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-6/4/S-14/R	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-6/4/S-25/R	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-6/4/S-50/R	G	15,250±150(50ft)	Silver	15,250-15,260mm

Title Modular cable - Straight/Reversed 6P4C 50µ", 26AWG, Silver, 5-50 feet ASSMANN WSW-No. AT-S-26-6/4/S-xx/R Drawing-No. rev00 Sheet 1/1
--