

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AT-S-26-4/4/B-25/R](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																										
A					"L"					A																																							
B					"L"					B																																							
C					<p>Note:</p> <ul style="list-style-type: none"> Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate. 				C																																								
D	<p>Conductor: [26AWG(0.16/7)Bare Copper]x4C Insulation: [PP6331 ID:0.95±0.03]x4C Jacket: PVC NOUL 65P</p> <p>Black Red Green Yellow</p>				<p>A, B, C, D</p>				D																																								
E	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%; text-align:center;">P1</td> <td style="width:50%; text-align:center;">P2</td> </tr> <tr> <td style="text-align:center;">1 — BLACK — 1</td> <td style="text-align:center;">1</td> </tr> <tr> <td style="text-align:center;">2 — RED — 2</td> <td style="text-align:center;">2</td> </tr> <tr> <td style="text-align:center;">3 — GREEN — 3</td> <td style="text-align:center;">3</td> </tr> <tr> <td style="text-align:center;">4 — YELLOW — 4</td> <td style="text-align:center;">4</td> </tr> </table>				P1	P2	1 — BLACK — 1	1	2 — RED — 2	2	3 — GREEN — 3	3	4 — YELLOW — 4	4	<p>E, F, G</p>				E																														
P1	P2																																																
1 — BLACK — 1	1																																																
2 — RED — 2	2																																																
3 — GREEN — 3	3																																																
4 — YELLOW — 4	4																																																
F					<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Part Number</th> <th>Drawing Number</th> <th>Wire Length "L"</th> <th>Jacket Color</th> <th>Cut Length</th> </tr> </thead> <tbody> <tr> <td>AT-S-26-4/4/B-5/R</td> <td>A</td> <td>1,525±20(5ft)</td> <td>Black</td> <td>1,525-1,535mm</td> </tr> <tr> <td>AT-S-26-4/4/B-7/R</td> <td>B</td> <td>2,135±30(7ft)</td> <td>Black</td> <td>2,135-2,145mm</td> </tr> <tr> <td>AT-S-26-4/4/B-10/R</td> <td>C</td> <td>3,050±60(10ft)</td> <td>Black</td> <td>3,050-3,060mm</td> </tr> <tr> <td>AT-S-26-4/4/B-12/R</td> <td>D</td> <td>3,660±60(12ft)</td> <td>Black</td> <td>3,660-3,670mm</td> </tr> <tr> <td>AT-S-26-4/4/B-14/R</td> <td>E</td> <td>4,270±60(14ft)</td> <td>Black</td> <td>4,270-4,280mm</td> </tr> <tr> <td>AT-S-26-4/4/B-25/R</td> <td>F</td> <td>7,625±100(25ft)</td> <td>Black</td> <td>7,625-7,635mm</td> </tr> <tr> <td>AT-S-26-4/4/B-50/R</td> <td>G</td> <td>15,250±150(50ft)</td> <td>Black</td> <td>15,250-15,260mm</td> </tr> </tbody> </table>				Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-4/4/B-5/R	A	1,525±20(5ft)	Black	1,525-1,535mm	AT-S-26-4/4/B-7/R	B	2,135±30(7ft)	Black	2,135-2,145mm	AT-S-26-4/4/B-10/R	C	3,050±60(10ft)	Black	3,050-3,060mm	AT-S-26-4/4/B-12/R	D	3,660±60(12ft)	Black	3,660-3,670mm	AT-S-26-4/4/B-14/R	E	4,270±60(14ft)	Black	4,270-4,280mm	AT-S-26-4/4/B-25/R	F	7,625±100(25ft)	Black	7,625-7,635mm	AT-S-26-4/4/B-50/R	G	15,250±150(50ft)	Black	15,250-15,260mm	F
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																													
AT-S-26-4/4/B-5/R	A	1,525±20(5ft)	Black	1,525-1,535mm																																													
AT-S-26-4/4/B-7/R	B	2,135±30(7ft)	Black	2,135-2,145mm																																													
AT-S-26-4/4/B-10/R	C	3,050±60(10ft)	Black	3,050-3,060mm																																													
AT-S-26-4/4/B-12/R	D	3,660±60(12ft)	Black	3,660-3,670mm																																													
AT-S-26-4/4/B-14/R	E	4,270±60(14ft)	Black	4,270-4,280mm																																													
AT-S-26-4/4/B-25/R	F	7,625±100(25ft)	Black	7,625-7,635mm																																													
AT-S-26-4/4/B-50/R	G	15,250±150(50ft)	Black	15,250-15,260mm																																													
G	<p>Scale Free</p> <p>TOLERANCE</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>X.</td> <td>±X</td> </tr> <tr> <td>X.X</td> <td>±X</td> </tr> <tr> <td>X.XX</td> <td>±X</td> </tr> <tr> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>X.°</td> <td>±X°</td> </tr> <tr> <td>X.X°</td> <td>±X°</td> </tr> <tr> <td>Angle</td> <td>TOL</td> </tr> </table>				X.	±X	X.X	±X	X.XX	±X	DIM	TOL	X.°	±X°	X.X°	±X°	Angle	TOL	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>Date</td> <td>Name</td> <td>Title</td> </tr> <tr> <td>27.06.13</td> <td>Wilson</td> <td>Modular cable - Straight/Reversed 4P4C 50µ", 26AWG, Black, 5-50 feet</td> </tr> <tr> <td>27.06.13</td> <td>Groll</td> <td>ASSMANN WSW-No. AT-S-26-4/4/B-xx/R</td> </tr> <tr> <td colspan="2">Drawing-No.</td> <td>rev00</td> </tr> <tr> <td colspan="2">Replace</td> <td>Sheet 1/1</td> </tr> </table>				Date	Name	Title	27.06.13	Wilson	Modular cable - Straight/Reversed 4P4C 50µ", 26AWG, Black, 5-50 feet	27.06.13	Groll	ASSMANN WSW-No. AT-S-26-4/4/B-xx/R	Drawing-No.		rev00	Replace		Sheet 1/1	G											
X.	±X																																																
X.X	±X																																																
X.XX	±X																																																
DIM	TOL																																																
X.°	±X°																																																
X.X°	±X°																																																
Angle	TOL																																																
Date	Name	Title																																															
27.06.13	Wilson	Modular cable - Straight/Reversed 4P4C 50µ", 26AWG, Black, 5-50 feet																																															
27.06.13	Groll	ASSMANN WSW-No. AT-S-26-4/4/B-xx/R																																															
Drawing-No.		rev00																																															
Replace		Sheet 1/1																																															
H	<p>Unit: mm</p>				<p>1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us</p>				H																																								
1	2	3	4	5	6	7	7	7																																									