

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)  
[AT-S-26-4/4/S-7-OE](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																																																																																		
A								A																																																																																																	
B								B																																																																																																	
C	<p><b>P1</b></p>							C																																																																																																	
D	<p>Conductor: [26AWG(0.16/7)Bare Copper]x4C          Insulation: [PP6331 ID:0.95±0.03]x4C          Jacket: PVC NOUL 65P</p> <p>Black Red Green Yellow</p>							D																																																																																																	
E	<p><b>SEC: A-A</b></p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align:center;">P1</td> <td style="text-align:center;">P2</td> </tr> <tr> <td style="text-align:center;">1 BLACK</td> <td style="text-align:center;">1</td> </tr> <tr> <td style="text-align:center;">2 RED</td> <td style="text-align:center;">2</td> </tr> <tr> <td style="text-align:center;">3 GREEN</td> <td style="text-align:center;">3</td> </tr> <tr> <td style="text-align:center;">4 YELLOW</td> <td style="text-align:center;">4</td> </tr> </table>							P1	P2	1 BLACK	1	2 RED	2	3 GREEN	3	4 YELLOW	4	E																																																																																							
P1	P2																																																																																																								
1 BLACK	1																																																																																																								
2 RED	2																																																																																																								
3 GREEN	3																																																																																																								
4 YELLOW	4																																																																																																								
F	<p>120±10 A, B, C, D</p> <p>140±10 E, F, G</p>							F																																																																																																	
G	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th>Date</th> <th>Name</th> <th>Title</th> </tr> </thead> <tbody> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>28.06.13</td> <td>Wilson</td> <td>Modular cable - Straight/Open 4P4C 50µ", 26AWG, Silver, 5-50 feet</td> </tr> <tr> <td>X.</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td>Approved</td> <td>28.06.13</td> <td>Groll</td> <td>ASSMANN WSW-No. AT-S-26-4/4/S-xx-OE</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>rev00</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Sheet</td> </tr> <tr> <td>X.°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1/1</td> </tr> <tr> <td>X.X°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="2" rowspan="2"> </td> <td>Replace</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	28.06.13	Wilson	Modular cable - Straight/Open 4P4C 50µ", 26AWG, Silver, 5-50 feet	X.	±X					Approved	28.06.13	Groll	ASSMANN WSW-No. AT-S-26-4/4/S-xx-OE	X.X	±X								Drawing-No.	X.XX	±X								rev00	DIM	TOL								Sheet	X.°	±X°								1/1	X.X°	±X°									Angle	TOL	Id.	Modification	Date	Name			Replace										G
Scale	Free					Date	Name	Title																																																																																																	
TOLERANCE						Drawn	28.06.13	Wilson	Modular cable - Straight/Open 4P4C 50µ", 26AWG, Silver, 5-50 feet																																																																																																
X.	±X					Approved	28.06.13	Groll	ASSMANN WSW-No. AT-S-26-4/4/S-xx-OE																																																																																																
X.X	±X								Drawing-No.																																																																																																
X.XX	±X								rev00																																																																																																
DIM	TOL								Sheet																																																																																																
X.°	±X°								1/1																																																																																																
X.X°	±X°																																																																																																								
Angle	TOL	Id.	Modification	Date	Name			Replace																																																																																																	
H	<p>Unit: mm</p> <div style="border: 1px solid black; padding: 5px; display: inline-block;"> <p><b>RoHS</b> Compliant</p> </div>							H																																																																																																	

**Note:**

- Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-4/4/S-5-OE	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-4/4/S-7-OE	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-4/4/S-10-OE	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-4/4/S-12-OE	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-4/4/S-14-OE	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-4/4/S-25-OE	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-4/4/S-50-OE	G	15,250±150(50ft)	Silver	15,250-15,260mm



1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@assmann.us