

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)  
[AT-S-26-6/6/S-7-OE](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																																																									
A								A																																																																								
B								B																																																																								
C	<p><b>P1</b></p> <p>Conductor: [26AWG(0.16/7)Bare Copper]x6C          Insulation: [PP6331 ID:0.95±0.03]x6C          Jacket: PVC NOUL 65P</p>							C																																																																								
D	<p>White Black Red Green Yellow Blue</p>							D																																																																								
E	<table border="1" style="border-collapse: collapse;"> <thead> <tr> <th>P1</th> <th>COLOR</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>WHITE</td> </tr> <tr> <td>2</td> <td>BLACK</td> </tr> <tr> <td>3</td> <td>RED</td> </tr> <tr> <td>4</td> <td>GREEN</td> </tr> <tr> <td>5</td> <td>YELLOW</td> </tr> <tr> <td>6</td> <td>BLUE</td> </tr> </tbody> </table>							P1	COLOR	1	WHITE	2	BLACK	3	RED	4	GREEN	5	YELLOW	6	BLUE	E																																																										
P1	COLOR																																																																															
1	WHITE																																																																															
2	BLACK																																																																															
3	RED																																																																															
4	GREEN																																																																															
5	YELLOW																																																																															
6	BLUE																																																																															
F								F																																																																								
G	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Part Number</th> <th>Drawing Number</th> <th>Wire Length "L"</th> <th>Jacket Color</th> <th>Cut Length</th> </tr> </thead> <tbody> <tr> <td>AT-S-26-6/6/S-5-OE</td> <td>A</td> <td>1,525±20(5ft)</td> <td>Silver</td> <td>1,525-1,535mm</td> </tr> <tr> <td>AT-S-26-6/6/S-7-OE</td> <td>B</td> <td>2,135±30(7ft)</td> <td>Silver</td> <td>2,135-2,145mm</td> </tr> <tr> <td>AT-S-26-6/6/S-10-OE</td> <td>C</td> <td>3,050±60(10ft)</td> <td>Silver</td> <td>3,050-3,060mm</td> </tr> <tr> <td>AT-S-26-6/6/S-12-OE</td> <td>D</td> <td>3,660±60(12ft)</td> <td>Silver</td> <td>3,660-3,670mm</td> </tr> <tr> <td>AT-S-26-6/6/S-14-OE</td> <td>E</td> <td>4,270±60(14ft)</td> <td>Silver</td> <td>4,270-4,280mm</td> </tr> <tr> <td>AT-S-26-6/6/S-25-OE</td> <td>F</td> <td>7,625±100(25ft)</td> <td>Silver</td> <td>7,625-7,635mm</td> </tr> <tr> <td>AT-S-26-6/6/S-50-OE</td> <td>G</td> <td>15,250±150(50ft)</td> <td>Silver</td> <td>15,250-15,260mm</td> </tr> </tbody> </table>							Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-6/6/S-5-OE	A	1,525±20(5ft)	Silver	1,525-1,535mm	AT-S-26-6/6/S-7-OE	B	2,135±30(7ft)	Silver	2,135-2,145mm	AT-S-26-6/6/S-10-OE	C	3,050±60(10ft)	Silver	3,050-3,060mm	AT-S-26-6/6/S-12-OE	D	3,660±60(12ft)	Silver	3,660-3,670mm	AT-S-26-6/6/S-14-OE	E	4,270±60(14ft)	Silver	4,270-4,280mm	AT-S-26-6/6/S-25-OE	F	7,625±100(25ft)	Silver	7,625-7,635mm	AT-S-26-6/6/S-50-OE	G	15,250±150(50ft)	Silver	15,250-15,260mm	G																																
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																																												
AT-S-26-6/6/S-5-OE	A	1,525±20(5ft)	Silver	1,525-1,535mm																																																																												
AT-S-26-6/6/S-7-OE	B	2,135±30(7ft)	Silver	2,135-2,145mm																																																																												
AT-S-26-6/6/S-10-OE	C	3,050±60(10ft)	Silver	3,050-3,060mm																																																																												
AT-S-26-6/6/S-12-OE	D	3,660±60(12ft)	Silver	3,660-3,670mm																																																																												
AT-S-26-6/6/S-14-OE	E	4,270±60(14ft)	Silver	4,270-4,280mm																																																																												
AT-S-26-6/6/S-25-OE	F	7,625±100(25ft)	Silver	7,625-7,635mm																																																																												
AT-S-26-6/6/S-50-OE	G	15,250±150(50ft)	Silver	15,250-15,260mm																																																																												
H	<p>Unit: mm</p> <div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>RoHS</b> Compliant         </div> <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th>Scale</th> <th>Free</th> <th colspan="3"></th> <th>Date</th> <th>Name</th> <th rowspan="2">Title Modular cable - Straight/Open 6P6C 50µ", 26AWG, Silver, 5-50 feet</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>28.06.13</td> <td>Wilson</td> </tr> <tr> <td>X.</td> <td>±X</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>28.06.13</td> <td>Groll</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X°</td> <td>±X°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td></td> </tr> </tbody> </table> <div style="text-align: right; margin-top: 10px;"> </div>							Scale	Free				Date	Name	Title Modular cable - Straight/Open 6P6C 50µ", 26AWG, Silver, 5-50 feet	TOLERANCE					Drawn	28.06.13	Wilson	X.	±X				Approved	28.06.13	Groll	X.X	±X							X.XX	±X							DIM	TOL							X.°	±X°							X.X°	±X°							Angle	TOL	Id.	Modification	Date	Name			H
Scale	Free				Date	Name	Title Modular cable - Straight/Open 6P6C 50µ", 26AWG, Silver, 5-50 feet																																																																									
TOLERANCE					Drawn	28.06.13		Wilson																																																																								
X.	±X				Approved	28.06.13	Groll																																																																									
X.X	±X																																																																															
X.XX	±X																																																																															
DIM	TOL																																																																															
X.°	±X°																																																																															
X.X°	±X°																																																																															
Angle	TOL	Id.	Modification	Date	Name																																																																											

**Note:**

- Material: Housing-polycarbonate, clear
- Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/S-5-OE	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-6/6/S-7-OE	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-6/6/S-10-OE	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-6/6/S-12-OE	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-6/6/S-14-OE	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-6/6/S-25-OE	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-6/6/S-50-OE	G	15,250±150(50ft)	Silver	15,250-15,260mm



1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@assmann.us

Drawing-No.	rev00
Replace	Sheet 1/1