

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Skyetek Inc](#)

[SM-MA-MH](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

*physical made digital*

## Product Overview

The SkyeModule™ M10 leads the industry in embedded UHF reader price-performance. Offering a one-of-a-kind combination of high performance, low cost, and compact footprint, the M10 delivers the following benefits:

- **Price-performance** through read performance that reaches up to 5 meters.
- **Inventory reliability** through anti-collision that allows up to 50 tags to be read in a single read operation.
- **Compact size**, with approximately 40% smaller footprint than most other 1 watt reader modules.
- **Ease of integration** by using SkyeAPI, a single library that abstracts, simplifies, and automates tag and protocol-specific functions from the host system.
- **Investment protection** through SkyeOS permitting field firmware upgrades that allow for future tag introductions and protocol enhancements.
- **TagIQ®** support for a broad array of EPC Class 1 Gen 2 tags allowing for maximum application flexibility and optimization.
- **TagIQ™** that accounts for tag-specific characteristics so as to optimize read/write performance for individual tag types.
- **Performance optimization** achieved through power control (10 – 30 dBm), noise reduction technology, and power management.

## Applications

The SkyeModule M10 has been created specifically for several applications and use cases that share common requirements for tag support, protocol and performance. The M10 is an ideal solution for:

- **Applications**
  - o Inventory Management
  - o Asset Tracking
  - o Patron Management
  - o Worker Tracking
- **Use Cases**
  - o Handheld / Mobile Readers
  - o Doorway Readers
  - o Printers / Encoders
  - o Smart-Cabinets / -Shelves

## FEATURES

- » UHF Band, 860-960 MHz
- » 30 dBm max output power
- » Broad support for EPC C1G2 tag vendors
- » Compact size
- » Field upgradeable firmware
- » Variety of host interfaces: UART (TTL), USB, SPI & I2C
- » API support in ANSI-C, .NET, ASCII, and binary

## BENEFITS

- » Industry-leading price performance
- » Designed for item-level inventory / asset management applications
- » Simple integration for fast time-to-market
- » Common software interface with other SkyeModules for maximum design flexibility
- » Designed for technology investment protection

» [www.skyetek.com](http://www.skyetek.com)**About SkyeTek:**

SkyeTek transforms traditional RFID into a networking technology enabling goods and assets to participate in a connected world.

SkyeTek develops readers that serve as intelligent edge devices and software that binds policies to tagged items. By extending networks to the physical world, our customers increase revenue through their ability to predict demand, prevent counterfeiting, and personalize user interactions.

SkyeTek combines intelligent software with an inexpensive hardware platform to provide a modern RFID security model, distributed policy management engine, and network-ready readers. Enterprises deploy SkyeTek's solutions to deliver a seamless RFID edge network capable of centralized management and real-time response for applications in item tracking, product authentication, access control, and patron management.

**For more information:**

1525 Market Street, Ste 200 Denver,  
Colorado 80202 USA  
ph: 720.328.3425

[www.skyetek.com](http://www.skyetek.com)



**Copyright © 2005-2009 SkyeTek, Inc.**  
SkyeTek®, Tagnostic®, SkyeWare™, Physical made Digital™, TagQTM, ReaderDNATM, SkyeModuleTM and AURATM are trademarks or registered trademarks of SkyeTek, Inc. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice. ver. 080506

**SkyeModule M10****Software**

SkyeAPI C/.NET  
SkyeTek Protocol v3  
SkyeWare 4 Developer/Demo

SkyeOS™ firmware with Fast Inventory anti-collision, secure key store and bootloader for field upgrades.

**Tag Support**

Protocol	Verified Manufacturers
EPC C1G2 / ISO18000-6C Planned*: IPX, EM4122, EM4444 ISO18000-6B	Alien, Atmel, Avery Dennison, Hitachi, Impinj, NXP, Omron, TI, UPM Raflatac/Rafsec EM Microelectronics

**Specifications**

Frequency 860-960 MHz	Air Interface Protocols EPC C1G2 / ISO 18000-6C: 40, 80, 160 kbps Planned*: ISO 18000-6B: 40 kbps IPX EM EM4122, EM4444: 64, 256	Read Performance Read range up to 5 meters for a single tag. Anti-collision performance up to 50 tags/second. Performance assumes 6 dBi linearly-polarized antenna and is dependent on tag type, configuration, and other
Physical Length: 1.69 inches; 42.8 mm Width: 3.01 inches; 76.5 mm Height: 0.44 inches; 11.2 mm Weight:	Antenna Connection 50 Ω port with MMCX (female) VSWR 1.5:1 or lower for best performance	
Environment Storage Temperature: -30°C to 85°C Operating Temperature: 5°C	Current Consumption Idle/Sleep Mode: 462 mA Scan Mode: 1.5 A @ 30	
Host Communication UART(TTL): 9.6-115.2 Kbps USB 2.0 Full Speed: 12 Mbps 4 programmable	Supply Voltage 3.3 V, regulated	
Regulatory Support FCC 15.247, RoHS Planned*: ETIS 302-208, China,	Output Power Adjustable 10-30 dBm with 0.1 dB steps Power Accuracy: ±1 dBm	

\* Additional support for regulatory regions, tag protocols, and communication rates will be supported soon after initial release – please contact your sales representative for more information.

**DKM10 - SkyeModule M10 Developer Kit**

The developer kit for the SkyeModule M10 includes all hardware and software components required to integrate UHF RFID technology quickly and easily into an application:

Hardware	Software	Service
1 M10 SkyeModule	SkyeWare 4	Technical
1 Host Interface Board	SkyAPI: C/.NET	
1 860-960MHz External Antenna	SkyeTek Protocol	
1 6V Power Supply		
1 RS-232 Cable		
1 USB Cable		
SkyeTek sample tag kit		

**SkyeTek Reader Technology** SkyeTek provides a variety of reader technology at both 13.56 MHz (HF) and 860 - 960 MHz (UHF). ReaderDNA, a comprehensive reference design, is available for component level integration of the technology including complete design files, BOM, and test fixture. All SkyeTek readers leverage powerful firmware that drastically reduce hardware costs and are delivered in conjunction with ReaderDNA. SkyeModules are controlled via the SkyeTek Protocol, a powerful but simple communication protocol that grants the user access to all features of an RFID transponder. Further, they have been designed with flexible and modular embedded software that allows one to select only the features desired.

