

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[ICS93772AFT](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



English | 简体中文 | 日本語

Search Entire Site

Contact IDT | Investors | Press

[About IDT](#) | 
 [Products](#) | 
 [Applications](#) | 
 [Support](#) | 
 [myIDT](#)

[Document Search](#) | 
 [Package Search](#) | 
 [Parametric Search](#) | 
 [Cross Reference Search](#) | 
 [Green & RoHS](#) | 
 [Calculators](#) | 
 [Thermal Data](#) | 
 [Reliability & Quality](#) | 
 [Military](#)

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > DDR I and DDR II Buffers > Zero Delay Buffers > 93772 > 93772AFT

[Add to myIDT \[?\]](#)

You may also like...

## 93772AFT

**Category:** Zero Delay Buffers

**Generic Part:** 93772

**Market Group:** PC CLOCK

**Description:** PC BUFFER

Product Description/Features:   
 • Low skew, low jitter PLL clock driver   
 • Max frequency supported = 266MHz (DDR 533)   
 • I2C for functional and output control   
 • Feedback pins for input to output synchronization   
 • Spread Spectrum tolerant inputs   
 • 3.3V tolerant CLK\_INT input



### Parameters

Package	SSOP 28 (PY28)
Voltage	3.3 V
Package	SSOP 28
Speed	NA
Temperature	C
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	240°C
Rebake Conditions	N/A
Length	10.2
Mark	R
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active