

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[ICS952911BF](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Home > Products > > 952911 > 952911BF

[Add to myIDT \[?\]](#)

You may also like...

## 952911BF

### Category:

**Generic Part:** 952911

**Market Group:** PC CLOCK

**Description:** PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features:  $\hat{\epsilon}$  2 - 0.7V current-mode differential CPU pairs  $\hat{\epsilon}$  10 - PCI, 3 free running, 33MHz  $\hat{\epsilon}$  3 - REF, 14.318MHz  $\hat{\epsilon}$  3 - 3V66, 66.66MHz  $\hat{\epsilon}$  1 - 48MHz  $\hat{\epsilon}$  1 - 24/48MHz  $\hat{\epsilon}$  2 - 25MHz @ 2.5V



### Parameters

Package	SSOP 48 (PV48)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	120
Factory Order Increment	30

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	225°C
Rebake Conditions	N/A
Length	15.9
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active