

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)
[952911BFLFT](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Home > Products > > 952911 > 952911BFLFT

[Add to myIDT \[?\]](#)

You may also like...

952911BFLFT

Category:

Generic Part: 952911

Market Group: PC CLOCK

Description: PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIAPT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: â€¢ 2 - 0.7V current-mode differential CPU pairs â€¢ 10 - PCI, 3 free running, 33MHz â€¢ 3 - REF, 14.318MHz â€¢ 3 - 3V66, 66.66MHz â€¢ 1 - 48MHz â€¢ 1 - 24/48MHz â€¢ 2 - 25MHz @ 2.5V



Parameters

| | |
|-------------------------|-----------------|
| Package | SSOP 48 (PVG48) |
| Speed | NA |
| Temperature | C |
| Voltage | 3.3 V |
| Status | Active |
| Sample | No |
| Minimum Order Quantity | 1000 |
| Factory Order Increment | 1000 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Type | Title | Size | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |

Package

| | |
|----------------------------------|--------------------------|
| Description | SSOP 300 MIL, 48LD |
| Class | PLASTIC |
| Moisture Sensitivity Level (MSL) | 1 |
| Category | Green |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH |
| Peak Reflow Temperature | 260°C |
| Rebake Conditions | N/A |
| Length | 15.9 |
| Mark | PVG |
| Width | 7.5 |
| Pitch | 0.64 |
| Thickness | 2.3 |
| Status | Active |