

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[952911BGLF](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



[Home](#) > [Products](#) > > 952911 > 952911BGLF

[Add to myIDT \[?\]](#)

You may also like...

## 952911BGLF

### Category:

**Generic Part:** 952911

**Market Group:** PC CLOCK

**Description:** PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features:  $\phi$  2 - 0.7V current-mode differential CPU pairs  $\phi$  10 - PCI, 3 free running, 33MHz  $\phi$  3 - REF, 14.318MHz  $\phi$  3 - 3V66, 66.66MHz  $\phi$  1 - 48MHz  $\phi$  1 - 24/48MHz  $\phi$  2 - 25MHz @ 2.5V



### Parameters

Package	TSSOP 48 (PAG48)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	114
Factory Order Increment	38

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	TSSOP 6.10 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	N/A
Length	12.5
Mark	G
Width	6.1
Pitch	0.5
Thickness	1.0
Status	Active