Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Integrated Device Technology (IDT) ICS953401CFLFT

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of Integrated Device Technology (IDT): Excellent Integrated System Limited

Datasheet of ICS953401CFLFT - IC TIMING CTRL HUB P4 56-SSOP

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com



English | 简体中文 | 日本語

▶ GO Search Entire Site

Support

Contact IDT | Investors | Press

myIDT

About IDT

Products

Applications

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets > 953401 > 953401CFLFT

Add to myIDT [?]

953401CFLFT

Category: **Desktop Chipsets**

Generic Part: 953401 PC CLOCK Market Group: PC MAIN CLOCK Description:

The ICS953401 is a two chip clock solution for desktop designs using SIS 656/662 style chipsets. When used with a zero delay buffer such as the ICS9P931 for DDR applications it provides all the necessary clocks signals for such a

system.

Output Features:

- 2 Pairs of differential CPUCLKs (differential current mode)
- 1 Pair of differential SRCCLK (differential current mode)
- 5 Pairs of differential PCI-Express clocks
- 8 PCI @ 3.3V, 2 free-running
- 2 ZCLKs @ 3.3V
- 1-12/48MHZ @ 3.3V selectable by I2C
- 1-24/48MHz, @ 3.3V selectable by I2C
- 3 REF @ 3.3V, 14.318MHz.



Parameters

Package	SSOP 56 (PVG56)
Voltage	3.3 V
Package	SSOP 56
Speed	NA
Temperature	С
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 56LD	
Class	PLASTIC	
Moisture Sensitivity Level (MSL)	1	
Category	Green	
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH	
Peak Reflow Temprature	260°C	
Rebake Conditions	N/A	
Length	18.4	
Mark	G	
Width	7.5	
Pitch	0.64	
Thickness	2.3	
Status	Active	