

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Integrated Device Technology \(IDT\)](#)  
[ICS9P750CFLFT](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > DDR I and DDR II Buffers > Zero Delay Buffers > 9P750 > 9P750CFLFT

[Add to myIDT \[?\]](#)

You may also like...

## 9P750CFLFT

**Category:** Zero Delay Buffers

**Generic Part:** 9P750

**Market Group:** PC CLOCK

**Description:** PC BUFFER

Recommended Application: DDR Zero Delay Clock Buffer Product Description/Features:  $\bullet$  Low skew, low jitter PLL clock driver  $\bullet$  12 pairs of differential outputs support up to DDR400  $\bullet$  Outputs divided into 3 groups - Group A is reference - Groups B and C have default offsets from Group A, but also have skew programmable in steps relative to Group A - Skew step (unit) set via RSTEP resistor  $\bullet$  Static Phase Offset (SPO) of entire device can be programmed - RSPO sets overall SPO (analog delay) - I2C register settings allow fine tuning in steps defined by RSTEP  $\bullet$  Spread spectrum tolerant inputs  $\bullet$  2.5 V differential reference clock input Switching Characteristics:  $\bullet$  PEAK - PEAK jitter (>100MHz): <75ps  $\bullet$  CYCLE - CYCLE jitter (>100MHz):<65ps  $\bullet$  OUTPUT - OUTPUT skew: <50ps  $\bullet$  DUTY CYCLE: 49% - 51%  $\bullet$  Slew rate: 1V/ns - 2V/ns  $\bullet$  Input clock duty cycle: 40% - 60%



### Parameters

Package	SSOP 48 (PVG48)
Voltage	3.3 V
Package	SSOP 48
Speed	NA
Temperature	C
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 300 ML, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	N/A
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active