

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:




[E-Switch](#)
[R1966ABLKBLKGF](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



POS. 1




PANEL THICKNESS	X dimension
0.75-1.25 [0.30-.049]	19.2-01 [0.756]
1.25-2.0 [0.49-.079]	19.4-01 [0.764]
2.0-3.0 [0.79-1.18]	19.8-01 [0.780]



PANEL CUTOUT
NOT TO SCALE

(B)

SWITCH FUNCTION	POS. 1	POS. 2
ON	DN	OFF
1-1a	OPEN	



CIRCUIT: SPST

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATING: 15A @ 125VAC OR 6A @ 250VAC
5. MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
6. ELECTRIC LIFE: 10,000 cycles
7. CONTACT RESISTANCE: <20 Mega Ω
8. INSULATION RESISTANCE: >1000 Mega Ω
9. DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles

E-SWITCH®

REV.	ECN No.	REVISION PART DESCRIPTION	DATE	CHKD
B	11664	REVISED PART DESCRIPTION	9/18/01	CJB

TITLE	SCALE	DATE	DR	DWG	REV
R1966A BLK BLK GF	1.5:1	1/9/95	LC	M301204	B

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSMITTED