

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK67501-0.5](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																																																																		
A								A																																																																																	
B								B																																																																																	
C								C																																																																																	
D	Material: - Cable: USB2.0 UL2725 [28AWG(7/0.12TC+AL:)*1P+ 28AWG(7/0.12TC)*2C]+AEB(48B TC) - Jacket: Black - OD: 3.5MM - P1 Connector: Micro USB 5P B/M Solder Type - Shell: Nickel - Pin: G/F - Insulator Color: Black - P2 Connector: Micro USB 5P A/M Solder Type - Shell: Nickel - Pin: G/F - Insulator Color: Black - Outer Jacket: Black PVC-40P							D																																																																																	
E	Electrical: 100% short, open, miswire test - Conduct resistance: 2Ω Max. - Insulation resistance: 10MΩ Min. - Dielectric test: 300V DC							E																																																																																	
F	PIN ASSIGNMENT							F																																																																																	
G	Unit: mm							G																																																																																	
H	<table border="1"> <thead> <tr> <th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Title</th></tr> </thead> <tbody> <tr> <td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>19.10.13</td><td>Chappell</td></tr> <tr> <td>X.</td><td>±0.3</td><td></td><td></td><td></td><td></td><td>Approved</td><td></td><td></td></tr> <tr> <td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.X°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>Angle</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table> 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	19.10.13	Chappell	X.	±0.3					Approved			X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°								Angle	TOL								H
Scale	Free					Date	Name	Title																																																																																	
TOLERANCE						Drawn	19.10.13	Chappell																																																																																	
X.	±0.3					Approved																																																																																			
X.X	±X																																																																																								
X.XX	±X																																																																																								
DIM	TOL																																																																																								
X.°	±X°																																																																																								
X.X°	±X°																																																																																								
Angle	TOL																																																																																								
	1	2	3	4	5	6	7																																																																																		