

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK3760-3-R](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																																											
A								A																																																										
B	<p><b>P1</b></p>					<p><b>P2</b></p>		B																																																										
C			<p><b>Material:</b></p>					C																																																										
D	<p><b>PIN OUT</b></p>		<p>.CABLE:28AWG(7/0.127 T.C)*3COAX(75 OHMS)+INSULATION:FO-PE INNER        JACKET:PVC OD:Ø2.5± 0.1mm(UL-1354)+28AWG(7/0.127 T.C)*4C+        INSULATION:SR-PVC ID:Ø0.85± 0.05mm(UL-1061)+AL/MY+DRAIN        WIRE:26AWG(7/0.16 T.C)+BRAID SHIELD(85%)+OUTER JACKET:PVC        COLOR:BEIGE OD:Ø8.1± 0.15mm UL-2919</p>					D																																																										
E			<p>.CONNECTOR:        P1&amp;P2:HDB 15P MALE,GOLD FLASH CONTACT,NICKEL PLATED SHELL        (9TH PIN UNLOAD)</p>					E																																																										
F			<p>.SHIELD:COPPER-FOIL 360° SOLDER TO CONNECTOR SHELL &amp; CABLE BRAID        .HOOD:MOLDED TYPE,PVC 45P,COLOR:BEIGE.        .ELECTRONIC TEST:        &lt;1&gt;.100% OPEN SHORT &amp; MIS WIRE TEST        &lt;2&gt;.CONTACT RESISTANCE 3 OHMS MAX.        &lt;3&gt;.INSULATION RESISTANCE 1M OHMS MIN/ DC 5V</p>					F																																																										
G			<p>.PACKING:SEE P-0039 REV.C PACKING DRAWING        (HANKING SIZE MUST BE SMALLER THAN PACKING)        PACKING TYPE: DB VP4.</p>					G																																																										
H			<table border="1"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td></td> <td>Name</td> <td rowspan="2">Item No. <b>AK3760-3</b></td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>10/26/12</td> </tr> <tr> <td>X.X</td> <td>±0.40</td> <td></td> <td></td> <td></td> <td></td> <td>Miller</td> <td rowspan="3">Title Premium VGA Monitor connection cable - HD D-Sub 15 pin Male &lt;=&gt; Male, 3 Meters</td> </tr> <tr> <td>X.XX</td> <td>±0.25</td> <td></td> <td></td> <td></td> <td></td> <td>Approved</td> <td>10/26/12</td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±3°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawing No.</td> <td><b>rev00</b></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Replace</td> <td>Sheet</td> </tr> </table>			Scale	1:1					Name	Item No. <b>AK3760-3</b>	TOLERANCE						Drawn	10/26/12	X.X	±0.40					Miller	Title Premium VGA Monitor connection cable - HD D-Sub 15 pin Male <=> Male, 3 Meters	X.XX	±0.25					Approved	10/26/12	X.XXX	±0.15							Angle	±3°						Drawing No.	<b>rev00</b>								Replace	Sheet			H
Scale	1:1					Name	Item No. <b>AK3760-3</b>																																																											
TOLERANCE						Drawn		10/26/12																																																										
X.X	±0.40					Miller	Title Premium VGA Monitor connection cable - HD D-Sub 15 pin Male <=> Male, 3 Meters																																																											
X.XX	±0.25					Approved		10/26/12																																																										
X.XXX	±0.15																																																																	
Angle	±3°						Drawing No.	<b>rev00</b>																																																										
							Replace	Sheet																																																										