

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Eaton \(formerly Cooper Bussmann\)](#)
[MPI4040R1-R10-R](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Technical Data **4086**

Effective October 2015

Supersedes April 2014

MPI4040

High current, high frequency, miniature power inductors



Applications

- Handheld/mobile devices
- Portable media players
- GPS/PDAs
- MP3 Players
- Battery operated devices
- Notebook/netbook/laptop
- Tablets/smartbooks
- LCD Displays
- LED Drivers
- POL Converters

Description

- Handles high transient inrush current spikes
- Magnetically shielded
- Frequency range 20kHz to 10MHz
- Inductance range from 0.10μH to 22μH
- Current range from 1.1A to 32.0A
- 4.7 x 4.31 footprint surface mount package in 1.2, 1.5, 1.85 or 2.0mm heights
- Rugged construction
- Halogen free, lead free, RoHS compliant

Environmental Data

- Storage temperature range (component): -55°C to +125°C
- Operating temperature range: -55°C to +125°C (Ambient plus self temperature rise)
- Solder reflow temperature: J-STD-020D compliant



Technical Data **4086**
 Effective October 2015

MPI4040
 High current, high frequency, miniature power inductors

Product Specifications

Part Number ⁵	OCL ¹ ± 20% (μH)	Part marking designator	I _{rms} ² (amps)	I _{sat} ³ @ 25°C (amps)	DCR (mΩ) ±20% @ 20°C	K-factor ⁴
R1 — 1.2mm Height						
MPI4040R1-R10-R	0.10	A	8.0	32 [†]	8.5	1401
MPI4040R1-R15-R	0.15	B	7.0	26 [†]	11	989
MPI4040R1-R22-R	0.23	C	5.5	21	18	814
MPI4040R1-R33-R	0.33	D	4.4	17	28	659
MPI4040R1-R47-R	0.47	E	5.2	11.5	20	1295
MPI4040R1-R68-R	0.68	F	3.3	9.0	51	461
MPI4040R1-1R0-R	1.0	G	3.7	7.7	40	990
MPI4040R1-1R5-R	1.5	H	3.0	6.5	60	732
MPI4040R1-2R2-R	2.2	I	2.6	5.9	80	623
MPI4040R1-3R3-R	3.3	J	2.2	5.1	115	481
MPI4040R1-4R7-R	4.7	K	1.8	3.8	180	411
MPI4040R1-6R8-R ^{††}	6.8	L	1.5	3.2	250	344
MPI4040R1-100-R ^{††}	10	M	1.2	2.8	370	276
R2 — 1.5mm Height						
MPI4040R2-R47-R	0.47	A	6.4	12.2	13	1403
MPI4040R2-1R0-R	1.0	B	4.6	8.9	25	935
MPI4040R2-1R5-R	1.5	C	3.8	7.6	37	701
MPI4040R2-2R2-R	2.2	D	3.2	5.7	58	647
MPI4040R2-3R3-R	3.3	E	2.6	5.4	76	495
MPI4040R2-4R7-R	4.7	F	2.2	4.3	105	421
MPI4040R2-6R8-R	6.8	G	1.8	3.4	158	351
MPI4040R2-100-R ^{††}	10.0	H	1.5	3.1	240	271

1. Open Circuit Inductance (OCL) Test Parameters: 100kHz, 0.10V_{rms}, 0.0Adc

2. I_{rms}: DC current for an approximate temperature rise of 40°C without core loss. De-rating is necessary for AC currents. Temperature rise is dependent upon several factors, including the PCB pad layout, trace thickness and width, air-flow and proximity to other heat generating components. It is recommended the part temperature not exceed 125°C under worst case operating conditions and therefore, the temperature rise should be verified in the end use application. I_{rms} testing was performed on a 19.05mm long x 6.35mm wide x 0.070mm thick copper trace in still air.

3. I_{sat}: Peak current for approximately 30% rolloff at +25°C.

4. K-factor: Used to determine B_{pp} for core loss (see graph).

B_{pp} = K * L * ΔI B_{pp}: (Gauss), K: (K-factor from table), L: (inductance in μH),
 ΔI = (peak-to-peak ripple current in amps).

5. Part Number Definition: MPI4040RX-XXX-R

- MPI4040R = product code and size
- X = version indicator
- XXX = inductance value in μH, R= decimal point - If no R is present, then last character equals the number of zeros
- -R suffix = RoHS compliant

† Transient pulse not to exceed 1 millisecond.

†† Maximum operating frequency less than 10MHz, consult factory for application specific values.

MPI4040

High current, high frequency, miniature power inductors

Technical Data **4086**
 Effective October 2015

Product Specifications

Part Number ⁵	OCL ¹ ± 20% (μH)	Part marking designator	I _{rms} ² (amps)	I _{sat} ³ @ 25°C (amps)	DCR (mΩ) ±20% @ 20°C	K-factor ⁴
R3 — 1.85mm Height						
MPI4040R3-R22-R	0.22	A	8.0	20	5.8	1870
MPI4040R3-R47-R	0.47	B	5.8	17	10.3	1530
MPI4040R3-1R2-R	1.2	C	4.0	9.4	32	732
MPI4040R3-1R5-R	1.5	D	3.8	8.2	36	673
MPI4040R3-2R2-R	2.2	E	3.4	7.9	48	543
MPI4040R3-3R3-R	3.3	F	3.0	6.6	60	432
MPI4040R3-4R7-R	4.7	G	2.3	4.8	92	374
MPI4040R3-6R8-R	6.8	H	2.0	4.5	120	306
MPI4040R3-100-R	10	I	1.5	3.8	213	251
MPI4040R3-150-R	15	J	1.3	3.0	285	213
MPI4040R3-220-R††	22	K	1.1	2.2	408	174
R4 — 2.0mm Height						
MPI4040R4-R22-R	0.22	A	10.1	15	5.3	2405
MPI4040R4-R33-R	0.33	B	9.5	12.8	6.0	1870
MPI4040R4-R47-R	0.45	C	8.1	11.5	8.2	1530
MPI4040R4-1R0-R	1.0	D	5.7	8.2	17	990
MPI4040R4-1R5-R	1.5	E	4.9	6.9	23	802
MPI4040R4-2R2-R	2.2	F	3.9	5.7	35	673
MPI4040R4-3R3-R††	3.3	G	3.3	4.5	49	510
MPI4040R4-4R7-R††	4.7	H	2.9	3.9	67	455
MPI4040R4-6R8-R††	6.8	I	2.4	3.2	91	374
MPI4040R4-100-R††	10	J	1.9	2.6	148	306
MPI4040R4-220-R††	22	K	1.3	1.8	316	203

1. Open Circuit Inductance (OCL) Test Parameters: 100kHz, 0.10Vrms, 0.0Aac

2. I_{rms}: DC current for an approximate temperature rise of 40°C without core loss. De-rating is necessary for AC currents. Temperature rise is dependent upon several factors, including the PCB pad layout, trace thickness and width, air-flow and proximity to other heat generating components. It is recommended the part temperature not exceed 125°C under worst case operating conditions and therefore, the temperature rise should be verified in the end use application. I_{rms} testing was performed on a 19.05mm long x 6.35mm wide x 0.070mm thick copper trace in still air.

3. I_{sat}: Peak current for approximately 30% rolloff at +25°C.

4. K-factor: Used to determine B_{pp} for core loss (see graph).

B_{pp} = K * L * DI.B_{pp}: (Gauss), K: (K-factor from table), L: (inductance in μH), DI = (peak-to-peak ripple current in amps).

5. Part Number Definition: MPI4040RX-XXX-R

- MPI4040R = product code and size
- X = version indicator
- XXX = inductance value in μH, R= decimal point - If no R is present, then last character equals the number of zeros
- -R suffix = RoHS compliant

† Transient pulse not to exceed 1 millisecond.




†† Maximum operating frequency less than 10MHz, consult factory for application specific values.

MPI4040


High current, high frequency, miniature power inductors

Technical Data **4086**
Effective October 2015


Dimensions (mm)



Recommended Pad Layout



Schematic



Part number	A Max
MPI4040R1-xxx-R	1.2
MPI4040R2-xxx-R	1.5
MPI4040R3-xxx-R	1.8
MPI4040R4-xxx-R	2.0

Part marking: xabcd

x = height: 1 = R1 (1.2mm), 2 = R2 (1.5mm), 3 = R3 (1.85mm), 4 = R4 (2.0mm)

a = Inductance value per the Part marking designator letter code in Product specification table.

b = Bi-weekly date code

c = Last digit of year manufactured

d = Revision level

Soldering surfaces to be coplanar within 0.10 millimeters

PCB tolerances are ±0.1 millimeters unless stated otherwise

Do not route traces or vias underneath the inductor

Packaging information (mm)


Supplied in tape and reel packaging:

MPI4040R1 = 5500 parts per 13" diameter reel

MPI4040R2 = 4500 parts per 13" diameter reel

MPI4040R3 = 3500 parts per 13" diameter reel

MPI4040R4 = 3000 parts per 13" diameter reel



MPI4040R1=1.30
MPI4040R2=1.60
MPI4040R3=1.95
MPI4040R4=2.1

SECTION A-A

User Direction of feed


Technical Data 4086

Effective October 2015





MPI4040

High current, high frequency, miniature power inductors

Temperature rise vs. total loss



Core loss



Technical Data 4086


Effective October 2015

MPI4040


High current, high frequency, miniature power inductors

1.2mm Height R1 inductance characteristics — % of OCL vs. I_{DC}


MPI4040R1-R10-R




MPI4040R1-R15-R




MPI4040R1-R22-R




MPI4040R1-R33-R



MPI4040R1-R47-R



MPI4040R1-R68-R










MPI4040

High current, high frequency, miniature power inductors

Technical Data 4086

Effective October 2015

1.2mm Height R1 inductance characteristics — % of OCL vs. I_{DC}











Technical Data 4086

Effective October 2015

MPI4040

High current, high frequency, miniature power inductors

1.5mm Height R2 inductance characteristics — % of OCL vs. I_{DC}



MPI4040


High current, high frequency, miniature power inductors

Technical Data 4086


Effective October 2015

1.85mm Height R3 inductance characteristics — % of OCL vs. I_{dc}


MPI4040R3-R22-R




MPI4040R3-R47-R




MPI4040R3-1R2-R




MPI4040R3-1R5-R



MPI4040R3-2R2-R



MPI4040R3-3R3-R



Technical Data 4086


Effective October 2015

MPI4040


High current, high frequency, miniature power inductors

1.85mm Height R3 inductance characteristics — % of OCL vs. I_{dc}


MPI4040R3-4R7-R




MPI4040R3-6R8-R




MPI4040R3-100-R



MPI4040R3-150-R



MPI4040R3-220-R











MPI4040

High current, high frequency, miniature power inductors

Technical Data **4086**

Effective October 2015

2.0mm Height R4 inductance characteristics — % of OCL vs. I_{DC}






Technical Data 4086

Effective October 2015

MPI4040

High current, high frequency, miniature power inductors

2.0mm Height R4 inductance characteristics — % of OCL vs. I_{DC}



MPI4040

High current, high frequency, miniature power inductors

Technical Data 4086
Effective October 2015

Solder reflow profile




Table 1 - Standard SnPb Solder (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_c)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_p to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/elx