

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Hammond Manufacturing](#)  
[1760F](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

1760F

NOTE: ALL LEADS 7" OUT MIN.

DIMENSIONS:	
A	3.250" ±0.063
B	1.687" ±0.125
C	1.995" ±0.063
D	2.813" ±0.063
G	0.187" ±0.015

PRIMARY	SECONDARY
BRN ○	WHT 16 Ω
RED ○	GRN 8 Ω
BLU ○	YEL 4 Ω
BLU ○	BLK COM

6950 Ω CT  
70Hz - 15kHz  
±1db (1kHz REF.)  
15W

ELECTRICAL DATA:	
Turns ratio:	29.19 : 1
Inductance	@240V,70Hz =>27.28H (Open circuit)
DCR	@ 20C, BLU - BRN = 120 Ω ±20%
	@ 20C, BLK - YEL = 0.171 Ω ±20%
	@ 20C, BLK - GRN = 0.245 Ω ±20%
	@ 20C, BLK - WHT= 0.476 Ω ±20%
FREQ. RESP	@ 15W(322.75V), 70Hz-15kHz, BLU-BRN ±1db (Ref.1kHz)
Pri. Impedance	6950 Ω CT(322.75V)
Sec. Impedance	4/8/16 Ω (7.746/10.95/15.49V)
Power	15 WATTS

**HAMMOND  
ELECTRONICS**

52 RANKIN PLACE,  
WATERLOO, ONTARIO, N2L 3Z5.  
PHONE (519) 886-6181  
FAX # (519) 886-9540

TITLE		1760F	
		DR BY	B.Pervaiz
		DATE	08/25/09
NO	DATE	REVISION	DIM IN(X)MM( )

1760F