

Excellent Integrated System Limited


Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Hammond Manufacturing](#)
[291EX](#)

For any questions, you can email us directly:

sales@integrated-circuit.com




291EX

NOTE: ALL LEADS 9" OUT MIN., STRIPPED .5"

DIMENSIONS:

A	3.438" ±0.063
B	4.063" ±0.125
C	4.125" ±0.063
D	1.844" ±0.063
E	2.750" ±0.063
F	3.438" ±0.063



ELECTRICAL DATA:

Turns ratio:	1 : 5.74 (RED - RED)
Exciting Current	@ 120V, 60Hz, BLK - WHT = 398mA Max.
DCR	@ 20C, BLK - WHT = 1.415 Ω ±20%
	@ 20C, RED - RED = 40.13 Ω ±20%
	@ 20C, GRN - GRN = 0.060 Ω ±20%
Pri. Voltage	120V 60Hz
Sec. Voltage (RMS)	660VCT @ 276mA C/W 53V TAP, 6.5V @ 3.15A
No Load Voltage	688.70VCT/ 6.78V



**HAMMOND
MANUFACTURING**

52 RANKIN PLACE,
WATERLOO, ONTARIO, N2L 3Z5.
PHONE (519) 886-6181
FAX # (519) 886-9540

TITLE

291EX

DR BY
B.Pervaiz

DATE
08/25/09

NO

DATE

REVISION

DIM IN(X)MM()

291EX