

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Hammond Manufacturing](#)  
[1422P8](#)


For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# Type 12 Mild Steel Two Door Wallmount Enclosure

## 1422 Series

### Continuous Hinge Door with Handle



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides a degree of protection from falling dirt, dust, oil and water.

### Standards

- UL 508 Type 12
- CSA Type 12
- Complies with
  - NEMA Type 12
  - IEC 60529, IP54

### Construction

- Enclosures are formed 12 or 14 gauge steel, as noted.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Body stiffeners are provided in enclosures 30" high or more for extra rigidity.
- Welded brackets provide for enclosure mounting.
- Gasketed overlapping doors eliminate the need for a center post.
- Continuously hinged doors may be removed by pulling the hinge pin.
- Doors are secured with a three point latch and operated with a key locking automotive type handle.
- Latch rods are equipped with rollers for easier door closing.
- Oil resistant gaskets are permanently secured.
- A removable 10 gauge inner panel is included in enclosures as noted.
- Smaller sizes include a 12 gauge inner panel.
- Collar studs are provided for mounting inner panels.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- A literature pocket is provided for the inside of the door.


### Finish

- Cover and enclosure are phosphatized and finished in recoatable smooth ANSI 61 gray powder coating on the outside, with white powder coating on the inside.
- Removable inner panel is finished in white powder coating.


### Accessories

- Inner Panels
- Blowers and Fans
- Door Stop Kit
- Cooling Products
- Ventilation
- Drip Shield Kit


- Enclosure Stabilizers
- Floor Stand Kit
- Heaters
- Type 1 Louvered Ventilating Plates
- Window Kits
- Filtered Fans
- Gland Plates
- Lighting
- Temperature Controls




**Front View**



**Side View**



**Section Y-Y**



**Stiffener Layout**  
1422UX12 & 1422WW12



**Section A-A**

1422VX12 & 1422WW12

**Section Z-Z**

(Except 1422VX12 & 1422WW12)

Part No.	A	B	C	Body Gauge	Panel Gauge	Panel Size		D	E	F	G	H	J	Ship Wt. (lbs)
1422P8	24.00	42.00	8.00	14	12	21.00	39.00	1.50	22.25	20.13	7.96	79		
1422PW8	24.00	48.00	8.00	14	12	21.00	45.00	1.50	22.25	23.13	7.96	92		
1422P10	24.00	42.00	10.00	14	12	21.00	39.00	1.50	22.25	20.13	9.96	101		
1422R10	30.00	42.00	10.00	14	12	27.00	39.00	1.50	28.25	20.13	9.96	112		
1422RW10	30.00	48.00	10.00	14	12	27.00	45.00	1.50	28.25	23.13	9.96	115		
1422RX10	30.00	60.00	10.00	14	12	27.00	57.00	1.50	28.25	29.13	9.96	142		
1422UV12	36.00	42.00	12.00	14	12	33.00	39.00	1.50	34.25	20.13	11.96	134		
1422UW12	36.00	48.00	12.00	14	12	33.00	45.00	1.50	34.25	23.13	11.96	230		
1422UX12	36.00	60.00	12.00	14	12	33.00	57.00	1.50	34.25	29.13	11.96	181		
1422VV12	42.00	42.00	12.00	14	12	39.00	39.00	1.50	40.25	20.13	11.96	152		
1422VW12	42.00	48.00	12.00	14	12	39.00	45.00	1.50	40.25	23.13	11.96	161		
1422VX12	42.13	60.06	12.69	12	10	38.00	56.00	2.00	40.25	29.13	11.96	202		
1422WW12	48.13	48.06	12.69	12	10	44.00	44.00	2.00	46.25	23.13	11.96	350		



**Distributor of Hammond Manufacturing: Excellent Integrated System Limited**

Datasheet of 1422P8 - BOX STEEL GRAY 24"L X 42"W

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

*Data subject to change without notice*

© 2016. Hammond Manufacturing Ltd. All rights reserved.