

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[AK672/3-2-R](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																					
A	USB 3.0 A/M 9Pin INS:Blue(PT 300C)					USB 3.0 B/M 9Pin INS:Blue(PT 300C)		A																																				
B	 <b>P1</b>					 <b>P2</b>		B																																				
C			<b>Material:</b> <ul style="list-style-type: none"> <li>Cable: UL-27725 [#28(7/0.127 T.C)*1P INS:Foam-PE+D.W (7.0127 T.C.)+AL/MY+Hot-melt-Mylar]*2C+#28(7/0.127 T.C)*1P INS:Polyolefin + #28(7/0.127 T.C)*2C INS:Polyolefin +AL/MY +B.D(85%)</li> <li>- PVC Jacket</li> <li>OD: 5.2±0.15MM</li> <li>- Color: Black</li> <li>• P1 Connector: USB 3.0 Type Male 9 Pin</li> <li>- Contact: 30µ"</li> <li>- Shell: Ni-Plated</li> <li>• P2 Connector: USB 3.0 Type Male 9 Pin</li> <li>- Contact: 30µ"</li> <li>- Shell: Ni-Plated</li> <li>• Hood: Molded Type, PVC 45P (Black)</li> </ul>					C																																				
D	<table border="1"> <thead> <tr> <th colspan="3">PIN OUT</th> </tr> </thead> <tbody> <tr> <td>P1</td> <td></td> <td>P2</td> </tr> <tr> <td>1</td> <td>RED</td> <td>1 PWR</td> </tr> <tr> <td>2</td> <td>WHITE</td> <td>2 UTP_D-</td> </tr> <tr> <td>3</td> <td>GREEN</td> <td>3 UTP_D+</td> </tr> <tr> <td>4</td> <td>BLACK</td> <td>4 GND_PWRrt</td> </tr> <tr> <td>5</td> <td>BLUE</td> <td>5 SDP1-</td> </tr> <tr> <td>6</td> <td>YELLOW</td> <td>6 SDP1+</td> </tr> <tr> <td>7</td> <td>D.W</td> <td>7 SDP1_Drain &amp; SDP2_Drain</td> </tr> <tr> <td>8</td> <td>PURPLE</td> <td>8 SDP2-</td> </tr> <tr> <td>9</td> <td>ORANGE</td> <td>9 SDP2+</td> </tr> <tr> <td>SHELL</td> <td>B.D</td> <td>SHELL</td> </tr> </tbody> </table>		PIN OUT			P1		P2	1	RED	1 PWR	2	WHITE	2 UTP_D-	3	GREEN	3 UTP_D+	4	BLACK	4 GND_PWRrt	5	BLUE	5 SDP1-	6	YELLOW	6 SDP1+	7	D.W	7 SDP1_Drain & SDP2_Drain	8	PURPLE	8 SDP2-	9	ORANGE	9 SDP2+	SHELL	B.D	SHELL						D
PIN OUT																																												
P1		P2																																										
1	RED	1 PWR																																										
2	WHITE	2 UTP_D-																																										
3	GREEN	3 UTP_D+																																										
4	BLACK	4 GND_PWRrt																																										
5	BLUE	5 SDP1-																																										
6	YELLOW	6 SDP1+																																										
7	D.W	7 SDP1_Drain & SDP2_Drain																																										
8	PURPLE	8 SDP2-																																										
9	ORANGE	9 SDP2+																																										
SHELL	B.D	SHELL																																										
E			<b>Electrical:</b> <ul style="list-style-type: none"> <li>• 100% Open short &amp; mis wire test</li> <li>Contact Resistance: 3Ω Max.</li> <li>Insulation Resistance: 10Ω Min.</li> <li>• Hi-Pot 300V DC</li> </ul>					E																																				
F						Unit: MM		F																																				
G	<table border="1"> <tr> <td>Scale</td> <td>1:1</td> </tr> <tr> <td colspan="2">TOLERANCE</td> </tr> <tr> <td>X.X</td> <td>±0.40</td> </tr> <tr> <td>X.XX</td> <td>±0.25</td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> </tr> <tr> <td>Angle</td> <td>±3°</td> </tr> </table>		Scale	1:1	TOLERANCE		X.X	±0.40	X.XX	±0.25	X.XXX	±0.15	Angle	±3°	<table border="1"> <tr> <td>Drawn</td> <td>01.04.12</td> <td>Name</td> <td>Chappell</td> </tr> <tr> <td>Approved</td> <td></td> <td></td> <td></td> </tr> </table>			Drawn	01.04.12	Name	Chappell	Approved				<table border="1"> <tr> <td>Item No.</td> <td><b>AK672/3-2</b></td> </tr> <tr> <td>Title</td> <td>USB 3.0 Cable, A Male &lt;=&gt; B Male, 9 Pin, Insulation Blue, 2 Meters</td> </tr> <tr> <td>Drawing No.</td> <td></td> </tr> <tr> <td>Replace</td> <td>rev00</td> </tr> <tr> <td>Sheet</td> <td></td> </tr> </table>		Item No.	<b>AK672/3-2</b>	Title	USB 3.0 Cable, A Male <=> B Male, 9 Pin, Insulation Blue, 2 Meters	Drawing No.		Replace	rev00	Sheet		G						
Scale	1:1																																											
TOLERANCE																																												
X.X	±0.40																																											
X.XX	±0.25																																											
X.XXX	±0.15																																											
Angle	±3°																																											
Drawn	01.04.12	Name	Chappell																																									
Approved																																												
Item No.	<b>AK672/3-2</b>																																											
Title	USB 3.0 Cable, A Male <=> B Male, 9 Pin, Insulation Blue, 2 Meters																																											
Drawing No.																																												
Replace	rev00																																											
Sheet																																												
H								H																																				
	1	2	3	4	5	6	7																																					