

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[0573555330](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



57355-5330ストレートアクション手動圧着工具 仕様書

57355-5330 STRAIGHT-ACTION HAND CRIMP TOOL PRODUCT SPECIFICATION

ATP-57355-5330JE
 2005/01/28, Rev.- B
 日本モレックス株式会社
 Molex Japan Co., Ltd.

1. 概要

Description

このツールは、モレックス社の圧着ターミナルに電線を圧着接続するために開発された、ストレートアクションの手動圧着工具(ロングハンドルタイプ)です。

ご使用前に、添付の手動圧着工具の取扱説明書(IS-0116)をお読み頂き、圧着作業手順と管理方法について熟知してから、本ハンドツールをご使用頂きますようお願い申し上げます。

This tool is a straight-action hand crimp tool (long-handle type), which is designed for crimp-connecting wires to crimp terminal of Molex.

Please take the time to read attached the operating manual (IS-0116) of Hand Crimp Tool, making sure you understand the crimping procedures and management method described it before attempting to operate this hand tool.

2. 仕様

Specifications

- 1) 工具名称: 57355 - 5330ストレートアクション手動圧着工具(ロングハンドル)
Tool name: 57355-5330 Straight-Action Hand Crimp Tool (Long-Handle)
- 2) 工具型番: 57355 - 5330
Tool number:
- 3) 外形寸法と重量: 290(横幅) × 90(奥行き) × 15(厚さ)mm、約500gf
Outer dimensions and weight: 290 (width) x 90 (depth) x 15 (thickness) mm, Approx. 500gf
- 4) 管理方法: クリンプハイト及び圧着部引張強度(詳細は該当圧着仕様書に記載)
Management method: Crimp height and crimp strength (Details are described to the corresponding crimp specification)
- 5) 適合ターミナルと適合電線:
Applicable terminal and wires:

ターミナル番号 Terminal number	適合電線サイズ Applicable wire size (AWG)	適合被覆外径 Applicable insulation outer diameter (mm)	絶縁被覆ストリップ寸法 Wire insulation strip length (mm)
56115	#12	3.8 MAX.	3.9-4.4
56114	#12	3.8 MAX.	3.9-4.4

3. 工具外観

Tool Appearance

