

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1515099](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

SAC-3P-M12MS/2,0-PUR/BI-1L-S

Order No.: 1515099



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1515099>

Sensor/Actuator cable, 3-position, PUR/PVC, Black RAL 9005, Plug, straight M12, A-coded, on Valve plug type B (11 mm), with 1 LED, connected with Z diode, Cable length: 2 m

Commercial data	
GTIN (EAN)	4017918924652
Note	Made-to-order
sales group	D114
Pack	5 pcs.
Customs tariff	85444290
Weight/Piece	0.14687 KG

Product notes

WEEE/RoHS-compliant since:
07/05/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Rated current at 40°C	4 A
Rated voltage	24 V
Number of positions	3
Volume resistance	≤ 15 mΩ

SAC-3P-M12MS/2,0-PUR/BI-1L-S Order No.: 1515099
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1515099>

Insulation resistance	≥ 100 MΩ
Length of cable	2 m

General characteristics

Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Insertion/withdrawal cycles	≥ 100
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ag
Valve plug contact insert material	PBT
Material, housing, valve plug	PBT
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	TPU (Flat gasket valve plug)
Status display	1 LED
Protective circuit/component	Z diode

Conductor data

Cable type	PUR/PVC black
Cable abbreviation	LiYY11Y-JZ
Conductor cross section	0.75 mm ²
AWG signal line	18
Conductor structure signal line	42x 0.15 mm
Core diameter including insulation	Approx. 1.8 mm
Thickness, insulation	Approx. 0.34 mm (Core insulation)
	Approx. 0.35 mm (Outer cable sheath)
	Approx. 0.3 mm (Inner sheath)
External cable diameter	5.90 mm
Wire colors	Black 1, black 2, green/yellow
External sheath, color	Black RAL 9005
Insulation resistance	≥ 1 MΩ*km


SAC-3P-M12MS/2,0-PUR/BI-1L-S Order No.: 1515099

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1515099>


Nominal voltage, conductor	300 V
Test voltage, conductor	2000 V
Overall twist	3 concentrically twisted wires
Outer sheath, material	PUR
Material, inner sheath	PVC
Material conductor insulation	PVC
Conductor material	Bare Cu litz wires
Smallest bending radius, movable installation	59 mm

Diagrams/Drawings

Dimensioned drawing




M12 x 1 male connector, straight



Valve connector, type BI

Circuit diagram




Contact assignment of M12 plug and valve connector


SAC-3P-M12MS/2,0-PUR/BI-1L-S Order No.: 1515099

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1515099>

Schematic diagram



Pin assignment M12 plug, 3-pos., valve connector



Valve connector pin assignment, type BI

SAC-3P-M12MS/2,0-PUR/BI-1L-S Order No.: 1515099

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1515099>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;