

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1519736](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

SAC-4P-M 8MS-M12FS

Order No.: 1519736

The illustration shows the 3-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1519736>

Adapter, from M8 male connector to M12 female connector, 4-pos.

Commercial data	
GTIN (EAN)	4046356019927
sales group	D116
Pack	1 pcs.
Customs tariff	85366990
Weight/Piece	0.0161 KG
Catalog page information	Page 105 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2008



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Rated current at 40°C	4 A
Rated voltage	30 V
Number of positions	4
Volume resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Ambient temperature (operation)	-25 °C ... 90 °C

SAC-4P-M 8MS-M12FS Order No.: 1519736

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1519736>

General characteristics

Standards/regulations	M12 male connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/IP67
Insertion/withdrawal cycles	≥ 100
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material of grip body	TPU, hardly inflammable, self-extinguishing
Material, knurls	Zinc die-cast, (nickel-plated)
Sealing material	NBR
Status display	No

Certificates / Approvals




Certification


CUL Listed, UL Listed

Diagrams/Drawings

Dimensioned drawing



Circuit diagram




Contact assignment of the M8/M12 adapter


SAC-4P-M 8MS-M12FS Order No.: 1519736

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1519736>

Schematic diagram



Pin assignment M8 plug, 4-pos., view male side



Pin assignment M12 socket, 4-pos., A-coded, view female side

Layout of connector pin assignments



SAC-4P-M 8MS-M12FS Order No.: 1519736
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1519736>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;