

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1532072](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Extract from the online catalog

SAC-5P- 4,0-400/MINFS

Order No.: 1532072



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1532072>

Sensor/Actuator cable, 5-position, PVC, Yellow RAL 1021, Free conductor end, on Socket, straight 7/8" 16UNF, A-coded, Cable length: 4 m

Commercial data	
GTIN (EAN)	 4 046356 025140
Note	Made-to-order
sales group	D142
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 106 (PC-2007)

Product notes

WEEE/RoHS-compliant since:
05/31/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Rated current at 40°C	5.6 A
Rated voltage	300 V
Number of positions	5
Volume resistance	≤ 5 mΩ

SAC-5P- 4,0-400/MINFS Order No.: 1532072

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1532072>

Insulation resistance	≥ 10 MΩ
Length of cable	4 m

General characteristics

Coding	A - standard
Surge voltage category	II
Pollution degree	2
Degree of protection	IP68
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PUR
Material of grip body	PUR
Material, knurls	Nickel-plated brass
Status display	No
Test voltage	2500 V

Conductor data

Cable type	PVC yellow IEC color code
Conductor cross section	0.75 mm ²
AWG signal line	18
Conductor structure signal line	41x 0.16 mm
External cable diameter	6.80 mm
Wire colors	Black, brown, blue, white, green/yellow
External sheath, color	Yellow RAL 1021
Outer sheath, material	PVC

Certificates / Approvals



Certification


CUL Listed, UL Listed

SAC-5P- 4,0-400/MINFS Order No.: 1532072

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1532072>


Diagrams/Drawings

Dimensioned drawing




7/8"-16UNF socket, straight

Circuit diagram



Contact assignment of 7/8" plugs/sockets, cable type 400

Schematic diagram



Pin assignment, socket, 7/8"-16UNF, 5-pos., view of female side

SAC-5P- 4,0-400/MINFS Order No.: 1532072

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1532072>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;