

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Texas Instruments
LMH730036/NOPB

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of Texas Instruments: Excellent Integrated System Limited

Datasheet of LMH730036/NOPB - BOARD EVAL DEBUGGING LMH6622MA

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

NOTES: UNLESS OTHERWISE SPECIFIED

MATERIAL: PER IPC-4101/24

- LAMINATE: HIGH-TEMPERATURE FR4
 FINISHED BOARD: .0020 +/-.0005 INCH OUTSIDE LAYERS, COPPER.
 ALL COPPER LAYERS MUST BE SPACED PER DETAIL "A".
 BOARD THICKNESS IS MEASURED INCLUDING TOP AND BOTTOM SIDES
 FINISHED COPPER. ANY TIN, TIN/LEAD OR GOLD PLATING, SOLDERMASK
 AND SILKSCREEN LEGEND MUST NOT BE INCLUDED IN FINISHED BOARD
 THEKELES THICKNESS.
- THE CONDUCTOR PATTERN MUST BE ETCHED USING ARTWORK 880011846-002 REV A SUPPLIED WITHIN FABRICATION FILES' ARCHIVE 885011846-002 REV A OR GREATER.
- ALL CONDUCTOR LAYERS MUST BE REGISTERED WITHIN +/- .005 INCH FROM TRUE POSITION. 3.
- ETCH TOLERANCES:
 - ALL EXTERNAL LAYERS CONDUCTOR WIDTH MUST BE WITHIN +/- .0015 INCH OR +/- 15% OF GERBER DATA, WHICHEVER IS SMALLER.
- BOARD MUST BE NC DRILLED USING DRILL DATA SUPPLIED.
- DRILL TOLERANCES AND HOLE SIZES ARE FOR FINISHED BOARD: ALL PLATED THROUGH HOLES TO .080 INCH ARE +/- .003 INCH. ALL PLATED THROUGH HOLES OVER .081 INCH ARE +/- .005 INCH. ALL NON-PLATED THROUGH HOLES ARE +/- .005 INCH.
- ALL HOLES MUST BE REGISTERED WITHIN +/-.003 INCH FROM TRUE POSITION.
- MINIMUM ANNULAR RING MUST BE .002 INCH.
- - PER MIL-C-14550, PLATED THROUGH HOLES MUST BE PLATED WITH .0008
 - MIN. TO .0015 INCH MAX. THICK COPPER. FINISH: IMMERSION GOLD: 2 TO 8 MICROINCHES GOLD OVER 120-240 MICROINCHES OF ELECTROLESS NICKEL.
- 10. WARP AND TWIST OF FINISHED BOARDS MUST NOT EXCEED .007 INCH PER INCH.
- SOLDERMASK: PER IPC-SM-840

 11A. SOLDERMASK BOTH TOP AND BOTTOM SIDES.

 11B. SOLDERMASK MUST CLEAR ALL LANDS CHOWN ON GERBER SOLDERMASK

 11B. SOLDERMASK MUST CLEAR ALL LANDS CHOWN ON GERBER SOLDERMASK


 - LAYERS, EXCEPT FOR BARREL TENTING ON 0.025 INCH VIA PADS.
 COLOR GREEN AND SOLVENT FREE.
 LIQUID PHOTO-IMAGEABLE MUST BE .0002 MIN. TO .0008 MAX. INCH THICK
 MEASURED OVER COPPER PLATING.
- SILKSCREEN TOP AND BOTTOM SIDES USING A GLOSSY WHITE, NONCONDUCTIVE, EPOXY BASED INK. NO SILKSCREEN ALLOWED ON GOLD AREAS, ON PADS OR IN HOLES.
- ROUTE BOARD OUTLINE, PER DRAWING DIMENSIONS.
- VENDOR MUST ENTER VENDOR'S IDENTITY, DATE CODE AND ANY OTHER IDENTIFICATION MARKS ON BOTTOM SIDE ETCH APPROXIMATELY WHERE SHOWN.
- OTHER VENDOR NOMENCLATURE OR MARKINGS SHOULD NOT BE ETCHED OR SILKSCREENED ON BOARD WITHOUT PRIOR PERMISSION. 15.

	REVISIONS						
REV	DESCRIPTION	DATE	APPD				
Α	Etch 002 Production Release	12/03/07					

- ALL VENDOR IN-PROCESS MARKINGS, QA STAMPS, ETC. MUST BE PLACED ON THE BOTTOM SIDE OF BOARD.
- FINISHED BOARD MUST MEET UL94V-0 RATING AND RoHS COMPLIANCE.
- DOCUMENTATION THAT MUST BE DELIVERED WITH BOARDS:

 18A. CROSS SECTION REPORT (SPACING BETWEEN COPPER LAYERS AND COPPER THICKNESS)
 - ELECTRICAL TEST CERTIFICATION OF COMPLIANCE (ACCORDANCE WITH IPC-ET-652 CLASS II)
 CERTIFICATION OF COMPLIANCE (BOARD HAS BEEN MANUFACTURED TO DRAWING REQUIREMENTS)

RoHS CERTIFICATE OF COMPLIANCE.



Board Fabrication Information				
	Smallest Feature			
Air Gap	.010 inch			
Trace Width	.015 inch			
Hole Size	.025 inch			
Pad Size	.024 x .06 inch			
Surface Mount	Top & Bottom			

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES

MATERIAL: SEE NOTES			DRAWN: Ernesto Rey	DATE: 03-Dec-07	Nelfoxal BOARD & SYSTEM BUSINESS OPERATIONS				
FINISH: SEE NOTES			CHECKED:	DATE:		PCB FABRICATION DRAWING			
TOLERANCES		ENGINEER:	DATE:	LMH730036 Eval					
1 PL	2 PL	3 PL	Bob Holtz		⊢	DRAWING: FF4		044040 000	_
±.02 ±.01 ±.005		DO NOT COPY, DISPLAY, OR USE		В		551	011846-002	Α	
		.01 ±.005	DRAWING WITHOUT AUTHORIZATION DO NOT SCALE DRAWING		SCAL	E: NON	ΙE	SHEET 1 OF 2	REV



Distributor of Texas Instruments: Excellent Integrated System Limited

Datasheet of LMH730036/NOPB - BOARD EVAL DEBUGGING LMH6622MA Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

