

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1965856](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog


MSTBW 2,5/ 4-G GYBN

Order No.: 1965856

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1965856>

Header, nominal current: 12 A, rated voltage: 250 V, pitch: 5.0 mm, no. of positions: 4, mounting: Soldering

Commercial data

| | |
|----------------|--|
| GTIN (EAN) |  4 017918 910808 |
| sales group | E110 |
| Pack | 50 pcs. |
| Customs tariff | 85366990 |

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals



Certification

CB, CSA, CUL, UL, VDE-PZI

MSTBW 2,5/ 4-G GYBN Order No.: 1965856
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1965856>

Accessories

| Item | Designation | Description |
|-----------------|-------------|--|
| Assembly | | |
| 1755477 | MSTB-BL | Keying cap, for forming sections, plugs onto header pin, green insulating material |

| Marking | | |
|----------------|-----------------------|---|
| 0804183 | SK 5/3,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks |

| Plug/Adapter | | |
|---------------------|---------|--|
| 1734401 | CR-MSTB | Coding section, inserted into the recess in the header or the inverted plug, red insulating material |

Additional products

| Item | Designation | Description |
|-----------------|-----------------|---|
| Assembly | | |
| 1909236 | FKCT 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1779851 | MSTBT 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |

| General | | |
|----------------|----------------------|---|
| 1910377 | FKC 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1909731 | FKCVR 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1910050 | FKCVW 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1779437 | FRONT-MSTB 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1754481 | MSTB 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |

MSTBW 2,5/ 4-G GYBN Order No.: 1965856<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1965856>

| | | |
|---------|------------------|---|
| 1765797 | MSTBP 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1792032 | MVSTBR 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1792540 | MVSTBW 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |
| 1768781 | SMSTB 2,5/ 4-ST | Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Color: green, Metal surface: Sn |

MSTBW 2,5/ 4-G GYBN Order No.: 1965856

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1965856>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;