

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1647006](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## HC-B 10-KMQ-73/O1STM25

Order No.: 1647006



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1647006>

HEAVYCON coupling housing B10, with double locking latch, height 73 mm, with thread 1x M25

Commercial data	
GTIN (EAN)	 4 017918 969417
Note	Made-to-order
sales group	D002
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 485 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
03/01/2006



<http://www.download.phoenixcontact.com>  
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

General data	
Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	73 mm
Width	43 mm
Length	73 mm


HC-B 10-KMQ-73/O1STM25 Order No.: 1647006

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1647006>

Housing type	Coupling housings
Locking type	With double locking latch
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

### Diagrams/Drawings

Dimensioned drawing



HC-B 10-KMQ-73/O1STM25 Order No.: 1647006

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1647006>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;