

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1604754](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## HC-B 10-SMQ-52/O2M25

Order No.: 1604754

Figure shows a product variant with a height of 74 mm



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604754>

HEAVYCON box mounting base B10, with double locking latch, height 52 mm, with supports 2xM25

Commercial data	
GTIN (EAN)	 4 017918 882488
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 485 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
01/18/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	52 mm
Width	52 mm
Length	93 mm

HC-B 10-SMQ-52/O2M25 Order No.: 1604754

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604754>

Housing type	Box mounting bases
Locking type	With double locking latch
Type of the screw connection	2x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

### Certificates / Approvals




Certification

GOST

### Diagrams/Drawings

Dimensioned drawing



HC-B 10-SMQ-52/O2M25 Order No.: 1604754

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604754>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;