

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1604786](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

HC-B 16-SMLD-67/O1M25

Order No.: 1604786



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604786>

HEAVYCON box mounting base B16, with single locking latch, height 67 mm, with support 1xM25, with cover

Commercial data	
GTIN (EAN)	 4 017918 881559
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 489 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Note	For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K
Design	B16
Height	67 mm
Width	57 mm
Length	117 mm

HC-B 16-SMLD-67/O1M25 Order No.: 1604786

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604786>

Housing type	Box mounting base with cover
Locking type	With single locking latch
Cable exit	Conductor exit direction to the left (looking into the open single locking latch)
Type of the screw connection	1x M25
Protective cover	Yes
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF
Material, protective cover	PA

Certificates / Approvals




Certification

GOST

Diagrams/Drawings

Dimensioned drawing



HC-B 16-SMLD-67/O1M25 Order No.: 1604786

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604786>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;