

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1645037](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

HC-B 16-TFL-76/O1STM25S


Order No.: 1645037

The illustration shows the version HC-B 16-TFL-76/O1STM40S



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1645037>

HEAVYCON sleeve housing B16, for single locking latch, height 76 mm, without support 1x M25, lateral conductor exit

Commercial data	
GTIN (EAN)	 4 017918 912895
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 488 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Note	For contact inserts HC-B16, BB32, D40, DD72, HS6, M, K
Design	B16
Height	76 mm
Width	43 mm


HC-B 16-TFL-76/O1STM25S Order No.: 1645037

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1645037>

Length	94 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray

Diagrams/Drawings

Dimensioned drawing



HC-B 16-TFL-76/O1STM25S Order No.: 1645037

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1645037>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;