

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1604743](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog


HC-B 10-KML-73/O1M25

Order No.: 1604743



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604743>

HEAVYCON coupling housing B10, with single locking latch, height 52 mm, with support 1x M25

Commercial data	
GTIN (EAN)	 4 017918 882037
sales group	D002
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 483 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
03/01/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	73 mm
Width	43 mm
Length	73 mm

HC-B 10-KML-73/O1M25 Order No.: 1604743

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604743>

Housing type	Coupling housings
Locking type	With single locking latch
Type of the screw connection	1x M25
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	High-grade steel, handle: PA-GF
Material grip body interlock	PA-GF

Certificates / Approvals




Certification

GOST

Diagrams/Drawings

Dimensioned drawing



HC-B 10-KML-73/O1M25 Order No.: 1604743

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1604743>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;