

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1646201](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## HC-M-KV-T-M32

Order No.: 1646201



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646201>

### Commercial data

GTIN (EAN)	 4 017918 941345
sales group	D092
Pack	10 pcs.
Customs tariff	74153300
Catalog page information	Page 524 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
04/07/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

Cable gland material	Nickel-plated brass
Material, pressure screw	Nickel-plated brass
Cable seal material	Perbunan
Material, O-ring	NBR
Wrench size, union nut	41 mm
Wrench size, support	40 mm

HC-M-KV-T-M32 Order No.: 1646201

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646201>

---

Thread type connection side 1	M32
Length of the connecting thread	8.00 mm
Conductor sealing range	18.00 mm ... 27.00 mm
Clamping range of the strain relief clip	20.00 mm ... 30.00 mm
Degree of protection	IP65
Color	silver
Ambient temperature (operation)	-20 °C ... 80 °C

### Diagrams/Drawings

Dimensioned drawing

---

HC-M-KV-T-M32 Order No.: 1646201

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646201>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;