

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2304652](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog


CABLE-D25SUB/B/2X14/200/TU812

Order No.: 2304652



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304652>

Splitting cable (1 x 25-pos. D-SUB female connector to 2 x 14-pos. FLK) for ABB S800 I/O, cable length: 2 m

Commercial data	
GTIN (EAN)	 4 017918 951375
Note	Made-to-order
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 189 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
03/06/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General	
Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 Ω /m

CABLE-D25SUB/B/2X14/200/TU812 Order No.: 2304652

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304652>

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions, control side	25
Number of connectors, control side	1
Number of positions, module side	14
Number of connectors, modul side	2
Fixed cable length	2 m
Single wire, cross section	0.14 mm ²
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.3 mm
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding	no

CABLE-D25SUB/B/2X14/200/TU812 Order No.: 2304652
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304652>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;