

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1663336](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog


CK1,6-ED-0,37ST AG

Order No.: 1663336



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663336>

Turned 1.6 crimp contact, individual male contact, core diameter 0.14 to 0.37 mm², silver-plated

Commercial data	
GTIN (EAN)	 4 017918 123147
sales group	D090
Pack	100 pcs.
Customs tariff	85366990
Catalog page information	Page 528 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
12/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Electrical characteristics	
Note	For HC-M-12, HC-M-EMC, HC-D, HC-DD and VC-D contact inserts, the quality of a crimp connection is determined by DIN EN 60 352-2
Ambient temperature (operation)	-40 °C ... 125 °C

CK1,6-ED-0,37ST AG Order No.: 1663336
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663336>

Mechanical characteristics

Conductor cross-section	0.14 mm ² ... 0.37 mm ²
Connection cross-section AWG	26 ... 22
Stripping length of the individual wire	8 mm
Insertion/withdrawal cycles	≥ 500

General characteristics

Type	Individual male contact
Series	HC-M-12
Connection method	Crimp connection

Material data

Contact material	Copper alloy
Contact surface material	hard-silver plated

Certificates / Approvals



Certification GOST, UL

Accessories


Item	Designation	Description
General		
1884869	VC-EW 1,6	Contact removal tool, for turned and rolled CK- 1.6-... contacts
Tools		
1676734	CK1,6/2,5-MWZ	Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections
1687419	CRIMPFOX-1,6/2,5-ED-4,0	Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

CK1,6-ED-0,37ST AG Order No.: 1663336

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663336>

Diagrams/Drawings

Dimensioned drawing



CK1,6-ED-0,37ST AG Order No.: 1663336

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663336>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;