

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1674804](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## CK2,5-ED-0,50ST AU

Order No.: 1674804



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674804>

Turned 2.5 crimp contact, individual male contact, core diameter 0.5 mm<sup>2</sup>, gold-plated

Commercial data	
GTIN (EAN)	 4 017918 135508
sales group	D090
Pack	100 pcs.
Customs tariff	74152900
Catalog page information	Page 528 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
02/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Electrical characteristics

Note	For HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers, the quality of a crimp connection is determined by the DIN EN 60 352-2, gold-plated contacts recommended for U > 5 V and I > 5 mA
Ambient temperature (operation)	-40 °C ... 125 °C

CK2,5-ED-0,50ST AU Order No.: 1674804

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674804>

#### Mechanical characteristics

Conductor cross-section	0.5 mm <sup>2</sup>
Connection cross-section AWG	20
Stripping length of the individual wire	7.5 mm (9.5 mm at HC-M-HV...)
Insertion/withdrawal cycles	≥ 500

#### General characteristics

Type	Individual male contact
Connection method	Crimp connection
Connection	for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers. The quality of a crimp connection is determined by the DIN EN 60 352-2. for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers, the quality of a crimp connection is determined by the DIN EN 60 352-2 Gold-plated contacts are recommended for U > 5 V and I > 5 mA.

#### Material data

Contact material	Copper alloy
Contact surface material	Hard gold-plated

#### Certificates / Approvals



Certification GOST, UL

#### Accessories


Item	Designation	Description
<b>Tools</b>		
1676734	CK1,6/2,5-MWZ	Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections
1662722	CK2,5-EWZ	Contact removal tool, for turned and rolled CK- 2.5-... contacts
1687419	CRIMPFOX-1,6/2,5-ED-4,0	Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

CK2,5-ED-0,50ST AU Order No.: 1674804

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674804>

## Diagrams/Drawings

Dimensioned drawing



CK2,5-ED-0,50ST AU Order No.: 1674804

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674804>

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;