

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2866077](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

EMD-SL-PH-400

Order No.: 2866077



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866077>

Monitoring relay for monitoring phase sequence, phase failure and asymmetry, 342...477 V AC, supply from measurement supply, 2 PDTs



Commercial data	
GTIN (EAN)	 4 017918 952679
sales group	H216
Pack	1 pcs.
Customs tariff	85364900
Catalog page information	Page 657 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
04/03/2009



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Increasingly higher demands are being placed on safety and system availability – across all sectors. Processes are becoming more and more complex, not only in mechanical engineering and the chemical industry, but also in plant and automation technology. Demands on power engineering are also increasing constantly.

Error-free and therefore cost-effective operation can only be achieved through continuous monitoring of important network and system parameters. Electronic monitoring relays in the EMD series are available for a wide range of monitoring tasks to avoid the consequences of errors or to keep them within limits.

EMD-SL-PH-400 Order No.: 2866077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866077>

The operating states are indicated using colored LEDs, errors that may occur can be sent to a control system via a floating contact or can shut down a part of the system. Some device versions are equipped with startup and response delays in order to briefly tolerate measured values outside the set monitoring range.

Technical data
Input data

Nominal input voltage U_N	400 V (3 N ~ 400/230 V)
Function	Phase sequence, phase failure, asymmetry
Min setting range of the voltage threshold value	342 V AC ... 477 V AC
Setting range for response delay	≤ 350 ms (fixed setting)
Setting range for starting delay	≤ 500 ms (fixed setting)
Asymmetry	Fixed, approx. 30%
Recovery time	< 100 ms

Contact side

Contact type	2 floating PDT contacts
Maximum switching voltage	250 V AC (in acc. with IEC 60664-1)
Interrupting rating (ohmic load) max.	750 VA (3 A/250 V AC, module aligned, ≤ 5 mm spacing) 1250 VA (5 A/250 V AC, module not aligned, ≥ 5 mm spacing)
Output fuse	5 A (fast-blow)

Power supply

Supply voltage	(From the measured voltage)
----------------	-----------------------------

General data

Width	22.5 mm
Height	90 mm
Depth	113 mm
Mechanical service life	Approx. 2×10^7 cycles
Operating mode	100% operating factor
Ambient temperature (operation)	-25 °C ... 55 °C -25 °C ... 40 °C (corresponds to UL 508)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Mounting position	Any
Assembly instructions	on TS 35 profile rail acc. to EN 60715
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Surge voltage category	III, basic insulation (as per EN 50178)
Housing insulation material	Polyamide PA, self-extinguishing

EMD-SL-PH-400 Order No.: 2866077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866077>

Color	green
Rated insulation voltage	300 V (According to EN 50178)
Conformance	CE-compliant
UL, USA / Canada	UL/C-UL listed UL 508

Connection data

Conductor cross section stranded min.	0.25 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	14
Stripping length	8 mm
Type of connection	Screw connection

Certificates / Approvals




Certification

CUL Listed, UL Listed

Diagrams/Drawings

Block diagram



EMD-SL-PH-400 Order No.: 2866077

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866077>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;