

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2943738](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

EMG 45-SD-D/LA/SI

Order No.: 2943738




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2943738>

Rail-mountable socket, with glow lamp and equipment fusing 5x 20 mm to max. 6.3 A; green housing



Commercial data

GTIN (EAN)	 4 017918 081287
sales group	H070
Pack	5 pcs.
Customs tariff	85366990
Catalog page information	Page 602 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
07/14/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	250 V AC
Nominal current I_N	6.3 A
Status display	Glow lamp or LED with preresistor

EMG 45-SD-D/LA/SI Order No.: 2943738

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2943738>

Contact material	CuZn37
For country-specific use in	D
Color	green
Insulating material	PC-F
Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Standards/regulations	IEC 83
	DIN 49440-1
Width	45 mm
Height	75 mm
Depth	70.5 mm

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M3

Certificates / Approvals



Certification

GOST, VDE-PZI

Accessories

Item	Designation	Description
------	-------------	-------------

Marking


2947035	EMG-GKS 12	Equipment marker, width 12 mm
2947585	EMG-SGKS 10	Equipment marker, narrow

EMG 45-SD-D/LA/SI Order No.: 2943738

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2943738>

Diagrams/Drawings

Circuit diagram



EMG 45-SD-D/LA/SI Order No.: 2943738

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2943738>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;