

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2316035](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## FB-PS-25/0.36A

Order No.: 2316035




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2316035>

Isolated Foundation Fieldbus Power Supply with integrated Terminator. Multiple single channel modules can be installed using Phoenix Contacts TBUS connector system reducing wiring and installation costs.



### Commercial data

GTIN (EAN)	 4 046356 298698
sales group	H682
Pack	1 pcs.
Customs tariff	85044082
Catalog page information	Page 499 (IF-2009)

<http://www.download.phoenixcontact.com>  
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Input data

DC input voltage range	19.2 V DC ... 35 V DC
------------------------	-----------------------

#### Output data

Output voltage range	25 V DC ... 27 V DC (on the trunk)
Output current	360 mA (on the trunk)

#### General data

Width	22.5 mm
-------	---------

FB-PS-25/0.36A Order No.: 2316035

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2316035>

Height	114.5 mm
Depth	108.3 mm
Net weight	210 g
Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (no condensation)
Mounting position	horizontal DIN rail NS 35, EN 60715

**Connection data, input**

Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

**Connection data, output**

Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

**Signaling**

Output name	Power OK
Status display	Green LED
Output name	OVERLOAD
Status display	LED red

**Certificates / Approvals**

Certification Ex: CUL-EX LIS, PxC-EX, UL-EX LIS

FB-PS-25/0.36A Order No.: 2316035


<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2316035>

**Accessories**

Item	Designation	Description
<b>General</b>		
2707437	ME 22,5 TBUS 1,5/ 5-ST-3,81 GN	DIN rail connector for current transducers, gold-plated contacts, for DIN rail mounting, 5-pos.
2856058	PT 1X2-24AC-ST	Protective plug PT with protective circuit for a 2-core floating signal circuit. Nominal voltage: 24 V AC
2856113	PT 1X2-BE	Base element for protective plug PT with protective circuit for a 2-core floating signal circuit. Mounting on NS 35/7.5 und NS 35/15, housing width: 17.5 mm.


**Diagrams/Drawings**

Block diagram



Connection diagram: FB-PS-25/0.36A

Dimensioned drawing



FB-PS-25/0.36A

FB-PS-25/0.36A Order No.: 2316035  
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2316035>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;