

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2290410](#)


For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

FLKM 14/8P/PLC

Order No.: 2290410



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290410>

VARIOFACE interface module, for 8 channels, each with an additional terminal block per signal for a common plus potential



Commercial data	
GTIN (EAN)	
sales group	I090
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 202 (IF-2007)

Product notes

WEEE/RoHS-compliant since:
09/11/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per branch	1 A
Max. total current of voltage supply	3 A

FLKM 14/8P/PLC Order No.: 2290410

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290410>

Number of positions	14
Width	57 mm
Height	90 mm
Depth	68 mm
Status display	No
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage	500 V (50 Hz, 1 min.)
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Pollution degree	2
Surge voltage category	II

Connection data

Connection 1	Field level
Type of connection	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3
Connection 2	Control system level
Number of connections	1
Type of connection	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of positions	14

Certificates / Approvals


Certification


CUL, GOST, UL

FLKM 14/8P/PLC Order No.: 2290410

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290410>

Diagrams/Drawings

Circuit diagram



Connection scheme: FLKM 14/8P/PLC

FLKM 14/8P/PLC Order No.: 2290410

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290410>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;