

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2302751](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



Extract from the online catalog


FLKM 14-PA-INLINE/IN16

Order No.: 2302751



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302751>

VARIOFACE front adapter for 16-channel Inline modules, input IB IL 24 DI 16

Commercial data	
GTIN (EAN)	 4 017918 929473
Note	Made-to-order
sales group	I661
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 227 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
03/30/2007



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.


Technical data	
General	
Nominal voltage U_N	< 50 V AC 60 V DC
Channels which can be connected	16
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13

FLKM 14-PA-INLINE/IN16 Order No.: 2302751
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302751>


Number of plug connectors	2
No. of positions, plug connector	14
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Max. permissible current	1 A (per path)
Supported controller	Phoenix Contact/Inline

Diagrams/Drawings

Connection diagram



Circuit diagram



Connection scheme: FLKM 14-PA-INLINE/IN16

FLKM 14-PA-INLINE/IN16 Order No.: 2302751

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302751>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;