

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2867649](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

RAD-CAB-EF393- 3M

Order No.: 2867649

The illustration shows a version of the product



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867649>

Antenna cable, 3 m in length; N (male) -> N (male), attenuation approx. 0.45 dB/m at 2.4 GHz; impedance 50 ohms

| Commercial data | |
|--------------------------|---------------------|
| GTIN (EAN) | 4 017918 939014 |
| sales group | H178 |
| Pack | 1 pcs. |
| Customs tariff | 85442000 |
| Catalog page information | Page 535 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
09/03/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| General | |
|--------------------|---------------------------|
| Connection 1 | Plug connector connection |
| Type of connection | Type N (male) |
| Fixed cable length | 3 m |
| Cable type | EF 393 |
| Cable, attenuation | approx. 0.45 dB/m |

RAD-CAB-EF393- 3M Order No.: 2867649

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867649>

| | |
|---------------------------------|---------------------------|
| Minimum bending radius | 50.00 mm |
| External diameter | 10.00 mm |
| Outer sheath, material | Radox (LSFH) |
| Connection name | Plug connector connection |
| Type of connection | Type N (male) |
| Note | Both sides |
| Ambient temperature (operation) | -40 °C ... 105 °C |

RAD-CAB-EF393- 3M Order No.: 2867649

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867649>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;