

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2285467](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog


## SFLY 2,5/D32

Order No.: 2285467



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2285467>

Screw socket, Nominal current: 4 A, Number of positions: 32, Pitch: 5.08 mm, Color: green

Commercial data	
GTIN (EAN)	 4 017918 055943
sales group	E311
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 532 (CC-2009)

### Product notes

WEEE/RoHS-compliant since:  
11/09/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

Dimensions / positions	
Length	39.8 mm
Height	32.4 mm
Width	95 mm
Pitch	5.08 mm
Number of positions	32

SFLY 2,5/D32 Order No.: 2285467

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2285467>

Hole diameter	2.8 mm
Screw thread	M3
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

**Technical data**

Range of articles	SFLY 2,5
Insulating material group	I
Rated surge voltage (III/3)	4 kV
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	4 A
Nominal voltage U <sub>N</sub>	250 V
Insulating material	PA
Inflammability class acc. to UL 94	V2
Stripping length	8 mm

**Connection data**

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

**Certificates / Approvals**



Certification


GOST

SFLY 2,5/D32 Order No.: 2285467

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2285467>

### Diagrams/Drawings

Dimensioned drawing



SFLY 2,5/D32 Order No.: 2285467

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2285467>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;