

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1655645](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

VS-ST-KX-75-LP

Order No.: 1655645



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655645>

Coaxial contact, for D-SUB combination inserts, for PCB assembly, pin, angled, gold-plated

Commercial data	
GTIN (EAN)	 4 046356 029537
Note	Made-to-order
sales group	D502
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 325 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
09/07/2006



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Mechanical characteristics	
Insertion/withdrawal cycles	≥ 500

VS-ST-KX-75-LP Order No.: 1655645

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655645>

Type of connection	PCB mounting
Insertion force per signal contact	≤ 7.00 N
Extraction force per signal contact	≤ 7 N
Ambient temperature (operation)	-55 °C ... 135 °C

Material data

Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

Electrical characteristics

Rated voltage (III/3)	250 V
Rated current	2 A
Insulation resistance	10 TΩ

Accessories

Item	Designation	Description
1676747	HC-M4-KOAX-EWZ	Contact removal tool for coaxial contacts

Tools

VS-ST-KX-75-LP Order No.: 1655645

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655645>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;