

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1608016](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online
catalog

VS-PPC-C1-RJ45-MNNA-PG9-8Q5

Item cannot be ordered online at present.

Order No.: 1608016



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1608016>

RJ45 connector, IP67, with push/pull interlocking (version 14), metal housing, 1 Gbps, 8-pos., QUICKON fast connection technology, for 26 ... 24 AWG 1-wire and 7-wire conductors



Ethernet

Commercial data	
GTIN (EAN)	
sales group	D512
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 194 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
01/01/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Mechanical characteristics	
Number of positions	8
Connection profile	RJ45 in acc. with IEC PAS 61076-3-117
Locking type	Push Pull

VS-PPC-C1-RJ45-MNNA-PG9-8Q5 Order No.: 1608016

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1608016>

Shielded	Yes
Insertion/withdrawal cycles	≥ 250
Type of connection	IDC fast connection
Conductor cross-section	0.13 mm ² ... 0.32 mm ² (solid)
	0.14 mm ² ... 0.36 mm ² (stranded)
Connection cross-section AWG	26 ... 22 (solid)
	26 ... 22 (stranded)
External cable diameter	5 mm ... 8 mm
Cable exit	Straight
Color	silver
Ambient temperature (operation)	-40 °C ... 70 °C

Material data

Inflammability class acc. to UL 94	V0
Housing material	Zinc die-cast
Housing surface material	Nickel-plated
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material	Metal
Material, O-ring	NBR
Cable seal material	TPE
Material, housing intermediate seal	NBR
Degree of protection	IP65/67

Electrical characteristics

Number of positions	8
Nominal voltage U_N	50 V
Nominal current I_N	1.75 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)
Rated current	1.75 A
Surge voltage category	I
Pollution degree	2

Certificates / Approvals

VS-PPC-C1-RJ45-MNNA-PG9-8Q5 Order No.: 1608016
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1608016>

Certification

CUL, UL

Accessories


Item	Designation	Description
------	-------------	-------------

Tools

1657407	VS-CABLE-STRIP-VARIO	Stripping tool, for the multi-level stripping of shielded cables
---------	----------------------	--

Diagrams/Drawings

Dimensioned drawing



Push-pull RJ45 connector IP65/67

VS-PPC-C1-RJ45-MNNA-PG9-8Q5 Order No.: 1608016
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1608016>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;