

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[TE Connectivity Raychem Circuit Protection
MINISMDC110-2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

Tyco / Electronics
Raychem Circuit Protection
 308 Constitution Drive
 Menlo Park, CA 94025-1164
 Phone: 800-227-4856
 Fax: 800-227-4866

PolySwitch®
PTC Devices
 Overcurrent Protection Device

PRODUCT: miniSMD110

DOCUMENT: SCD 23489
 PCN: 472815
 REV LETTER: H
 REV DATE: JUNE 10, 2002
 PAGE NO.: 1 OF 1

Specification Status:RELEASED

Maximum Electrical Rating

Voltage: 8V_{DC}
Short Circuit Current: 100A

Notes:

1. All terminations are tin/lead plated.
2. Devices can be wave soldered.
3. Drawing not to scale

Marking:



PART IDENTIFICATION

MANUFACTURER'S MARK




TABLE I. DIMENSIONS:

	A		B		C		D	E	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN	MAX
mm:	4.37	4.73	0.38	0.62	3.07	3.41	0.30	0.25	0.50
in:	(0.172)	(0.186)	(0.015)	(0.025)	(0.121)	(0.134)	(0.012)	(0.010)	(0.020)

TABLE II. PERFORMANCE RATINGS:

CURRENT RATINGS **			TIME TO TRIP ** @ 8.0A	RESISTANCE VALUES		TRIPPED-STATE POWER DISSIPATION **
AMPERES AT -40°C HOLD	AMPERES AT 20°C HOLD	AMPERES AT 60°C HOLD	SECONDS AT 20°C MAX	OHMS AT 20°C MIN	OHMS AT 20°C MAX*	WATTS AT 20°C MAX
1.60	1.10	0.71	0.3	0.04	0.21	1.2

* Maximum resistance is measured 1 hour after reflow

** Values Specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents: PS300, E. N. SMD1.0x.

Precedence:

This specification takes precedence over documents referenced herein.

Effectivity:

Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION:

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.