

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Multi-Tech Systems, Inc.](#)

[MTCBA-C1X-N16-NAM](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

MultiModem® CDMA

Cellular Modem

The MultiModem® CDMA cellular modem offers standards-based dual-band CDMA2000 1xRTT performance. This ready-to-deploy, standalone modem provides wireless data communication and integrates seamlessly with virtually any application. It is available with an RS-232 interface to cover your application needs. The MultiModem CDMA cellular modem is based on industry-standard open interfaces and can be desktop or panel mounted.


Features

- CDMA2000 1xRTT
- Dual-band 800/1900 MHz CDMA
- Supports Short Message Service such as text, UCS-2, point-to-point (MT/MO) and cell broadcast
- Available with RS-232 interface
- Packet data up to 153.6K bps
- Circuit-switched data up to 14.4K bps
- IS-95A, IS-95B backwards compatible
- SMA antenna connector
- Configured using CDMA AT commands
- Multiple LEDs provide ongoing operational status
- Over-the-Air activation
- Desktop or panel mounting
- CDG 1 and 2 certified
- Two-year warranty



Benefits

- Rugged industrial chassis
- RS-232 interface
- Carrier approved



Specifications

Packet Data Features

CDMA2000 1xRTT, up to 153.6K bps forward & reverse

Dual-band 800/1900 MHz

Circuit Switched Data

IS-95A, IS-95B up to 14.4K bps forward & reverse

SMS Features

Text, UCS-2, Point-to-Point (MO/MT), cell broadcast

Connectors

RF Antenna: 50 ohm SMA female

Power: 2.5mm miniature screw

RS-232: DE-15 female

Power Requirements

9V to 32VDC

Operating System Support

Windows XP/2003/Vista/2008/7 (32-bit/64-bit)

Linux

Physical Description

4.3" w x 2.4" d x 0.94" h 0.4 lbs

(11 cm w x 6.1 cm d x 2.4 cm h) 0.2 kg

Environment

Operating: -22° to +158° F (-30° to +70° C)

Storage: -40° to +185° F (-40° to +85° C)

Humidity: 20% to 90% RH noncondensing

Approvals

EMC Compliance: FCC Part 15 Class B

Radio Compliance: FCC Part 22, 24; RSS 132,133

Safety: UL 60950-1; cUL 60950-1; IEC 60950-1

Network: CDG 1&2

Ordering Information

Product	Description	Region
MTCBA-C1X*	800/1900 MHz CDMA Modem	Regional
Ordering Codes		
-N2	For Sprint Networks (USA)	
-N3	For Verizon Wireless Networks (USA)	
-N16	For Aeris Communications Networks (USA)	
-NAM	Includes US Style Power Plug	

* Use ordering codes for specific build options. Go to www.multitech.com for detailed product model numbers.

Services & Warranty

Multi-Tech's comprehensive Support Services programs offer a full array of options to suit your specific needs. These services are aimed at protecting your investment, extending the life of your solution or product, and reducing total cost of ownership. Our seasoned technical experts, with an average tenure of more than 10 years, can walk you through smooth installations, troubleshoot issues and help you with configurations. Products include a 2-year warranty that can be extended up to 5 years via Multi-Tech's Extended Warranty program, which offers the convenience of Overnight Service* for optimal uptime.

Extended Warranty & Overnight Services

To give you peace-of-mind and protect your investment, our Extended Warranty Service Plans ensure your Multi-Tech products are covered for 1, 2, or 3 years beyond the manufacturer's warranty with an optional Overnight Service plan*.

Installation Support

Multi-Tech's Installation Support Service delivers priority service with the ability to work one-on-one with an experienced Multi-Tech technical support engineer, to guide you through the installation process for our products.

Technical Support Services

At Multi-Tech, we're committed to providing you personalized attention and quality service while providing you a quick response to your product support needs. We have several options of support for you to choose from.

For additional information on Support Services as well as other service offerings, please contact your Multi-Tech representative or visit www.multitech.com/support.go.

* Overnight replacement service is currently available for U.S. customers.

World Headquarters

Multi-Tech Systems, Inc.
 2205 Woodale Drive
 Mounds View, MN 55112 U.S.A.
 Tel: 763-785-3500
 Toll-Free: 800-328-9717
 Email: sales@multitech.com
www.multitech.com

EMEA Headquarters

Multi-Tech Systems (EMEA)
 Unit 1, Thames Court
 2 Richfield Avenue
 Reading, Berkshire RG1 8EQ
 United Kingdom
 Tel: +(44) 118 959 7774
 Email: sales@multitech.co.uk

