

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Vishay/Siliconix](#)  
[SIA850DJ-T1-GE3](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

**New Product**



**SiA850DJ**

Vishay Siliconix

**N-Channel 190-V (D-S) MOSFET with 190-V Diode**

PRODUCT SUMMARY			
V <sub>DS</sub> (V)	R <sub>DS(on)</sub> (Ω)	I <sub>D</sub> (A) <sup>a</sup>	Q <sub>g</sub> (Typ.)
190	3.8 at V <sub>GS</sub> = 4.5 V	0.95	1.4 nC
	4.2 at V <sub>GS</sub> = 2.5 V	0.9	
	17 at V <sub>GS</sub> = 1.8 V	0.3	

DIODE PRODUCT SUMMARY		
V <sub>KA</sub> (V)	V <sub>f</sub> (V) Diode Forward Voltage	I <sub>F</sub> (A) <sup>a</sup>
190	1.2 at 0.5 A	0.95

**FEATURES**

- Halogen-free According to IEC 61249-2-21
- LITTLE FOOT® Plus Schottky Power MOSFET
- New Thermally Enhanced PowerPAK® SC-70 Package
  - Small Footprint Area
  - Low On-Resistance
  - Thin 0.75 mm profile




**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**


**APPLICATIONS**

- DC/DC Converter for Portable Devices
- Load Switch for Portable Devices


PowerPAK SC-70-6 Dual



Marking Code



Ordering Information: SiA850DJ-T1-GE3 (Lead (Pb)-free and Halogen-free)



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T <sub>A</sub> = 25 °C, unless otherwise noted				
Parameter	Symbol	Limit	Unit	
Drain-Source Voltage (MOSFET)	V <sub>DS</sub>	190	V	
Reverse Voltage (Diode)	V <sub>KA</sub>	190		
Gate-Source Voltage (MOSFET)	V <sub>GS</sub>	± 16	A	
Continuous Drain Current (T <sub>J</sub> = 150 °C) (MOSFET)	T <sub>C</sub> = 25 °C	0.95		
	T <sub>C</sub> = 70 °C	0.76		
	T <sub>A</sub> = 25 °C	0.47 <sup>b, c</sup>		
	T <sub>A</sub> = 70 °C	0.38 <sup>b, c</sup>		
Pulsed Drain Current (MOSFET)	I <sub>DM</sub>	1	W	
Continuous Source-Drain Diode Current (MOSFET Diode Conduction)	T <sub>C</sub> = 25 °C	0.95		
	T <sub>A</sub> = 25 °C	0.47 <sup>b, c</sup>		
Average Forward Current (Diode)	I <sub>F</sub>	0.95	W	
Pulsed Forward Current (Diode)	I <sub>FM</sub>	2		
Maximum Power Dissipation (MOSFET)	T <sub>C</sub> = 25 °C	7		
	T <sub>C</sub> = 70 °C	5		
	T <sub>A</sub> = 25 °C	1.9 <sup>b, c</sup>		
	T <sub>A</sub> = 70 °C	1.2 <sup>b, c</sup>		
Maximum Power Dissipation (Diode)	T <sub>C</sub> = 25 °C	7.8		
	T <sub>C</sub> = 70 °C	5		
	T <sub>A</sub> = 25 °C	1.9 <sup>b, c</sup>		
	T <sub>A</sub> = 70 °C	1.2 <sup>b, c</sup>		
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	- 55 to 150	°C	
Soldering Recommendations (Peak Temperature) <sup>d, e</sup>		260		

**New Product**

**SiA850DJ**

Vishay Siliconix



THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient (MOSFET) <sup>b, f</sup>	t ≤ 5 s	R <sub>thJA</sub>	52	65	°C/W
Maximum Junction-to-Case (Drain) (MOSFET)	Steady State	R <sub>thJC</sub>	12.5	16	
Maximum Junction-to-Ambient (Diode) <sup>b, f</sup>	t ≤ 5 s	R <sub>thJA</sub>	52	65	
Maximum Junction-to-Case (Drain) (Diode)	Steady State	R <sub>thJC</sub>	12.5	16	

Notes:

- a. T<sub>C</sub> = 25 °C.
- b. Surface Mounted on 1" x 1" FR4 board.
- c. t = 5 s.
- d. See Solder Profile ([www.vishay.com/ppg?73257](http://www.vishay.com/ppg?73257)). The PowerPAK SC-70 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- e. Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.
- f. Maximum under Steady State conditions is 110 °C/W.

SPECIFICATIONS T <sub>J</sub> = 25 °C, unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	V <sub>DS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA	190			V
V <sub>DS</sub> Temperature Coefficient	ΔV <sub>DS</sub> /T <sub>J</sub>	I <sub>D</sub> = 250 μA		200		mV/°C
V <sub>GS(th)</sub> Temperature Coefficient	ΔV <sub>GS(th)</sub> /T <sub>J</sub>			- 3.0		
Gate-Source Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA	0.6		1.4	V
Gate-Source Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ± 16 V			± 100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 190 V, V <sub>GS</sub> = 0 V			1	μA
		V <sub>DS</sub> = 190 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 85 °C			10	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> ≥ 5 V, V <sub>GS</sub> = 4.5 V	1			A
Drain-Source On-State Resistance <sup>a</sup>	R <sub>DS(on)</sub>	V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 0.36 A		3.0	3.8	Ω
		V <sub>GS</sub> = 2.5 V, I <sub>D</sub> = 0.35 A		3.2	4.2	
		V <sub>GS</sub> = 1.8 V, I <sub>D</sub> = 0.15 A		3.5	17.0	
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 15 V, I <sub>D</sub> = 0.36 A		2		S
<b>Dynamic<sup>b</sup></b>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 100 V, V <sub>GS</sub> = 0 V, f = 1 MHz		90		pF
Output Capacitance	C <sub>oss</sub>			5		
Reverse Transfer Capacitance	C <sub>rss</sub>			3		
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = 95 V, V <sub>GS</sub> = 10 V, I <sub>D</sub> = 0.47 A		3	4.5	nC
		V <sub>DS</sub> = 95 V, V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 0.47 A		1.4	2.1	
Gate-Source Charge	Q <sub>gs</sub>			0.25		
Gate-Drain Charge	Q <sub>gd</sub>		0.40			
Gate Resistance	R <sub>g</sub>	f = 1 MHz		2.3		Ω
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = 95 V, R <sub>L</sub> = 250 Ω I <sub>D</sub> ≅ 0.38 A, V <sub>GEN</sub> = 4.5 V, R <sub>g</sub> = 1 Ω		10	15	ns
Rise Time	t <sub>r</sub>			15	25	
Turn-Off DelayTime	t <sub>d(off)</sub>			25	40	
Fall Time	t <sub>f</sub>			15	25	
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = 95 V, R <sub>L</sub> = 250 Ω I <sub>D</sub> ≅ 0.38 A, V <sub>GEN</sub> = 10 V, R <sub>g</sub> = 1 Ω		3	10	
Rise Time	t <sub>r</sub>			12	20	
Turn-Off DelayTime	t <sub>d(off)</sub>			10	15	
Fall Time	t <sub>f</sub>			10	15	

**New Product**



**SiA850DJ**  
 Vishay Siliconix

<b>SPECIFICATIONS</b> $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
<b>Drain-Source Body Diode Characteristics</b>						
Continuous Source-Drain Diode Current	$I_S$	$T_C = 25\text{ }^\circ\text{C}$			0.95	A
Pulse Diode Forward Current	$I_{SM}$				1	
Body Diode Voltage	$V_{SD}$	$I_S = 0.5\text{ A}, V_{GS} = 0\text{ V}$		0.8	1.2	V
Body Diode Reverse Recovery Time	$t_{rr}$	$I_F = 0.5\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$		45	70	ns
Body Diode Reverse Recovery Charge	$Q_{rr}$			45	70	nC
Reverse Recovery Fall Time	$t_a$			21		ns
Reverse Recovery Rise Time	$t_b$			24		

Notes:

- a. Pulse test; pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .
- b. Guaranteed by design, not subject to production testing.

<b>DIODE SPECIFICATIONS</b> $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Voltage Drop	$V_F$	$I_F = 0.5\text{ A}$		0.82	1.2	V
		$I_F = 0.5\text{ A}, T_J = 125\text{ }^\circ\text{C}$		0.7	1.0	
Maximum Reverse Leakage Current	$I_{rm}$	$V_R = 190\text{ V}$			1	$\mu\text{A}$
		$V_R = 190\text{ V}, T_J = 85\text{ }^\circ\text{C}$			10	
Body Diode Reverse Recovery Time	$t_{rr}$	$I_F = 0.5\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$		45	70	ns
Body Diode Reverse Recovery Charge	$Q_{rr}$			45	70	nC
Reverse Recovery Fall Time	$t_a$			21		ns
Reverse Recovery Rise Time	$t_b$			24		

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


**New Product**

**SiA850DJ**


Vishay Siliconix




**DIODE TYPICAL CHARACTERISTICS**  $T_A = 25^\circ\text{C}$ , unless otherwise noted




**Reverse Current vs. Junction Temperature**



**Forward Diode Voltage**



**Normalized Thermal Transient Impedance, Junction-to-Ambient**




**Normalized Thermal Transient Impedance, Junction-to-Case**

**New Product**




**SiA850DJ**  
Vishay Siliconix


**MOSFET TYPICAL CHARACTERISTICS**  $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted




**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current**



**Capacitance**



**Gate Charge**



**On-Resistance vs. Junction Temperature**


**New Product**

**SiA850DJ**


Vishay Siliconix




**MOSFET TYPICAL CHARACTERISTICS**  $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted




**Source-Drain Diode Forward Voltage**




**On-Resistance vs. Gate-to-Source Voltage**



**Threshold Voltage**



**Single Pulse Power (Junction-to-Ambient)**



\*  $V_{GS} >$  minimum  $V_{GS}$  at which  $R_{DS(on)}$  is specified



**Safe Operating Area, Junction-to-Ambient**

**New Product**



**SiA850DJ**  
 Vishay Siliconix

**MOSFET TYPICAL CHARACTERISTICS**  $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted



\* The power dissipation  $P_D$  is based on  $T_{J(max)} = 150\text{ }^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.




**New Product**

**SiA850DJ**


Vishay Siliconix



**MOSFET TYPICAL CHARACTERISTICS**  $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted



**Normalized Thermal Transient Impedance, Junction-to-Ambient**



**Normalized Thermal Transient Impedance, Junction-to-Case**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?68909](http://www.vishay.com/ppg?68909).



## Legal Disclaimer Notice

Vishay

### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.