

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[1725055](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)




**Extract from the online catalog**

## PTDA 1,5/13-3,5

Order No.: 1725055

The figure shows a 10-position version of the product



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1725055>

PC terminal block, Nominal current: 13.5 A, Nom. voltage: 240 V, Pitch: 3.5 mm, Number of positions: 13, Connection method: Spring-cage conn., Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: green

### Commercial data

|                          |                    |
|--------------------------|--------------------|
| GTIN (EAN)               |                    |
| Note                     | Made-to-order      |
| sales group              | E411               |
| Pack                     | 50 pcs.            |
| Customs tariff           | 85369010           |
| Catalog page information | Page 455 (CC-2009) |

### Product notes

WEEE/RoHS-compliant since:  
02/21/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Dimensions / positions

|                     |        |
|---------------------|--------|
| Pitch               | 3.5 mm |
| Dimension a         | 42 mm  |
| Number of positions | 13     |

PTDA 1,5/13-3,5 Order No.: 1725055

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1725055>

|                |           |
|----------------|-----------|
| Pin dimensions | 1,0 x 0,4 |
| Pin spacing    | 3.5 mm    |
| Hole diameter  | 1.3 mm    |

#### Technical data

|                                     |                     |
|-------------------------------------|---------------------|
| Range of articles                   | PTDA 1,5/           |
| Insulating material group           | I                   |
| Rated surge voltage (III/3)         | 2.5 kV              |
| Rated surge voltage (III/2)         | 2.5 kV              |
| Rated surge voltage (II/2)          | 2.5 kV              |
| Rated voltage (III/3)               | 200 V               |
| Rated voltage (III/2)               | 240 V               |
| Rated voltage (II/2)                | 400 V               |
| Connection in acc. with standard    | EN-VDE              |
| Nominal current $I_N$               | 13.5 A              |
| Nominal cross section               | 1.5 mm <sup>2</sup> |
| Maximum load current                | 13.5 A              |
| Insulating material                 | PA                  |
| Inflammability class acc. to UL 94  | V0                  |
| Stripping length                    | 10 mm               |
| Nominal voltage, UL/CUL Use Group B | 300 V               |
| Nominal current, UL/CUL Use Group B | 12 A                |
| Nominal voltage, UL/CUL Use Group D | 300 V               |
| Nominal current, UL/CUL Use Group D | 10 A                |

#### Connection data

|                                                                            |                     |
|----------------------------------------------------------------------------|---------------------|
| Conductor cross section solid min.                                         | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup> |
| Conductor cross section stranded min.                                      | 0.2 mm <sup>2</sup> |
| Conductor cross section stranded max.                                      | 1.5 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.5 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.5 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 0.5 mm <sup>2</sup> |

PTDA 1,5/13-3,5 Order No.: 1725055

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1725055>

|                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|
| Conductor cross section AWG/kcmil min.                                                  | 24                  |
| Conductor cross section AWG/kcmil max                                                   | 16                  |
| 2 conductors with same cross section, solid min.                                        | 0.2 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                        | 1.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded min.                                     | 0.2 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup> |
| Minimum AWG according to UL/CUL                                                         | 24                  |
| Maximum AWG according to UL/CUL                                                         | 16                  |

#### Certificates / Approvals



Certification


CB, CCA, CUL, UL, VDE-PZI

PTDA 1,5/13-3,5 Order No.: 1725055


<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1725055>

## Diagrams/Drawings

Drilling plan/solder pad geometry




Diagram



Derating diagram for 5 positions; reduction factor=0.8

Dimensioned drawing



PTDA 1,5/13-3,5 Order No.: 1725055

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1725055>

---

#### Address

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;